

2580 Creekview Road Moab, Utah 84532 435/719-2018 435/719-2019 Fax

September 22, 2008

Fluid Minerals Group Bureau of Land Management Vernal Field Office 170 South 500 East Vernal, Utah 84078

RE: Application for Permit to Drill—XTO Energy, Inc.

RBU 22-21E

Surface Location: 2,133' FSL & 1,975' FWL, NE/4 SW/4,
Target Location: 2,570' FNL & 1,650' FWL, SW/4 NE/4, SE NUM
Section 21, T10S, R19E, SLB&M, Uintah County, Utah

Dear Fluid Minerals Group:

On behalf of XTO Energy, Inc. Buys & Associates, Inc. respectfully submits the enclosed original and three copies of the Application for Permit to Drill (APD) for the above referenced BLM surface and mineral directional well. The location of the surface and target location as well as all points along the intended well bore path are within Cause No. 259-01 and are not within 460 feet of any uncommitted tracts or the unit boundary. A letter from XTO Energy immediately follows this letter to charge the APD processing fee under the Fiscal Year 2008 Consolidated Appropriations Act. Included with the APD is the following supplemental information:

Exhibit "A" - Survey plats, layouts and photos of the proposed well site;

Exhibit "B" - Proposed location maps with access and utility corridors;

Exhibit "C" - Production site layout;

Exhibit "D" - Directional Drilling Plan with Directional Survey

Exhibit "E" - Surface Use Plan with APD Certification;

Exhibit "F" - Typical BOP and Choke Manifold diagram;

Exhibit "G" - Cultural and Paleontological Clearance Reports.

Thank you very much for your timely consideration of this application. Please feel free to contact myself or Ken Secrest of XTO Energy, Inc. at 435-722-4521 if you have any questions or need additional information.

Sincerely,

Don Hamilton

Agent for XTO Energy, Inc.

RECEIVED

SEP 2 5 2008

DIV. OF OIL, GAS & MINING

cc: Diana Mason, Division of Oil, Gas and Mining Ken Secrest, XTO Energy, Inc.



Form 3160-3 (February 2005) UNITED STATES			OMB No.	PPROVED 1004-0137 arch 31, 2007
DEPARTMENT OF THE BUREAU OF LAND MAN	INTERIOR		5. Lease Serial No. UTU-013766	
APPLICATION FOR PERMIT TO			6. If Indian, Allotee of N/A	or Tribe Name
la. Type of work: DRILL REENTI	ER		7 If Unit or CA Agree River Bend Uni	
lb. Type of Well: Oil Well Gas Well Other	Single Zone Multip	ple Zone	8. Lease Name and W RBU 22-21E	ell No.
2. Name of Operator XTO Energy, Inc.			9. API Well No. 43 C	47-40375
3a. Address PO Box 1360; 978 North Crescent Road Roosevelt, UT 84066	3b. Phone No. (include area code) 435-722-4521		10. Field and Pool, or E Natural Buttes	xploratory
4. Location of Well (Report location clearly and in accordance with an At surface 2,133' FSL & 1,975' FWL, NE/4 SV			11. Sec., T. R. M. or Bli	•
At proposed prod. zone 2,570' FNL & 1,650' FWL, SW/4 N	E4, SENW		Section 21, T10	S, R19E, SLB&M
14. Distance in miles and direction from nearest town or post office* 12.37 miles southwest of Ouray, Utah			12. County or Parish Uintah	13. State UT
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any) 1,975'	16. No. of acres in lease 2,240 acres	17. Spacin	g Unit dedicated to this w	ell
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20'	19. Proposed Depth 8,583' MD, 8,500' TVD	20. BLM/F	BIA Bond No. on file	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 5,188' GR	22. Approximate date work will star 12/15/2008	rt*	23. Estimated duration 14 days	
	24. Attachments			
 The following, completed in accordance with the requirements of Onshot Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest System SUPO must be filed with the appropriate Forest Service Office). 	4. Bond to cover the litem 20 above). Lands, the 5. Operator certific	he operation	s form: Is unless covered by an e Transition and/or plans as r	
25. Signature Don Hamilton	Name (Printed/Typed) Don Hamilton		I	Date 09/22/2008
Title Agent for XTO Effergy, Inc.				
Approved by (Stepature) Title	Name (Printed/Typed) Office RADLEY G			Date 10-09-09
Application approval does not warrant or certify that the applicant hold conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a	s legal or equitable title to those right	ts in the sub	ect lease which would en	
States any false, fictitious or fraudulent statements or representations as t *(Instructions on page 2)	o any matter within its jurisdiction.			
				•

Surs


603492X 44206214 39.931268 -109.788842 BHV 603387X 4420804Y 39.932930 -109.790040

RECEIVED SEP 2 5 2008

DIV. OF OIL, GAS & MINING

Federal Approval of this Action is Necessary

T10S, R19E, S.L.B.&M.



BASIS OF BEARINGS

BASIS OF BEARINGS IS A G.P.S. OBSERVATION.

LEGEND:

= PROPOSED WELL HEAD.

SECTION CORNERS LOCATED.

(NAD 83)

LATITUDE = 39'55'52.52" (39.931256) LONGITUDE = 109'47'22.79" (109.789664)

(NAD 27)


LATITUDE = 39°55′52.65" (39.931292) LONGITUDE = 109°47′20.28" (109.788967)

XTO ENERGY, INC.

Well location, RBU #22-21E, located as shown in the NE 1/4 SW 1/4 of Section 21, T10S, R19E, S.L.B.&M., Uintah County Utah.

BASIS OF ELEVATION

SPOT ELEVATION AT THE SOUTHWEST CORNER OF SECTION 20, T10S, R20E, S.L.B.&M., TAKEN FROM THE BIG PACK MTN. NW QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE QUAD. (TOPOGRAPHIC MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5251 FEET.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLATING PEPARED FROM FIELD NOTES OF ACTUAL SURVEYS AND BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELEF NO. 1614

RECISTEMEDALAND SURVEYOR REGISTRATION NO. 161319 STATE OF UTAH

UINTAH ENGINEERING & LAND SURVEYING 85 SOUTH 200 EAST - VERNAL, UTAH 84078 (435) 789-1017



REU 22-14E

COVER SHEET FOR ALL FEDERAL APDs

Dear BLM Office:

Re: Fiscal Year 2008 Consolidated Appropriations Act

Please charge the \$4000 APD fee to the credit card XTO has provided to the BLM office and send the receipt to:

Brenda Waller XTO Energy, Inc. 382 Road 3100 Aztec, NM 87410

Please contact me if anything further is needed at 505-215-0027.

Sincerely,

XTO Energy, Inc.

Brenda Waller

Brenda Waller

Manager of Regulatory Compliance

XTO ENERGY INC.

RBU 22-21E APD Data **September 16, 2008**

Location: 2133' FSL & 1975' FWL, Sec. 21, T10S, R19E

County: Uintah

State: Utah

Bottomhole Location: 2570' FNL & 1650' FWL, Sec. 21, T10S, R19E

GREATEST PROJECTED TD: 8583' MD/ 8500' TVD

OBJECTIVE: <u>Wasatch/Mesaverde</u>

APPROX GR ELEV: 5188'

Est KB ELEV: 5202' (14' AGL)

1. **MUD PROGRAM:**

INTERVAL	0' to 2252'	2252' to 8583'
HOLE SIZE	12.25"	7.875"
MUD TYPE	FW/Spud Mud	KCl Based LSND / Gel Chemical
WEIGHT	8.80 ppg	8.6-9.2 ppg
VISCOSITY	NC	30-60 sec-qt ⁻¹
WATER LOSS	NC	8-15 cc/30 min

Remarks: Use fibrous materials as needed to control seepage and lost circulation. Pump high viscosity sweeps as needed for hole cleaning. Raise viscosity at TD for logging. Reduce viscosity after logging for cementing purposes. The mud system will be monitored visually/manually.

CASING PROGRAM: 2.

Surface Casing: 9.625" casing set at ±2252'MD/2200'TVD in a 12.25" hole filled with 8.8 ppg mud

					Coll	Burst						
					Rating	Rating	Jt Str	ID	Drift	SF	SF	SF
Interval	Length	Wt	Gr	Cplg	(psi)	(psi)	(M-lbs)	(in)	(in)	Coll	Burst	Ten
0'-2252'	2252'	36#	J-55	ST&C	2020	3520	394	8.921	8.765	2.57	4.47	4.86

Production Casing: 5.5" casing set at ± 8583 'MD/8500'TVD in a 7.875" hole filled with 9.20 ppg mud.

					Coll	Burst						
					Rating	Rating	Jt Str	ID	Drift	SF	SF	SF
Interval	Length	Wt	Gr	Cplg	(psi)	(psi)	(M-lbs)	(in)	(in)	Coll	Burst	Ten
0'-8583'	8583'	17#	N-80	LT&C	6280	7740	348	4.892	4.767	1.95	2.41	2.39

Collapse and burst loads calculated at TVD with 0.1 psi/ft gas gradient back up.

3. **WELLHEAD:**

- A. Casing Head: Larkin Fig 92 (or equivalent), 9" nominal, 2,000 psig WP (4,000 psig test) with 9-5/8" 8rnd thread on bottom (or slip-on, weld-on) and 11-3/4" 8rnd thread on top.
- B. Tubing Head: Larkin Fig 612 (or equivalent), 6.456" nominal, 5,000 psig WP, 5-1/2" 8rnd female thread on bottom (or slip-on, weld-on), 8-5/8" 8rnd thread on top.

CEMENT PROGRAM:

A. Surface: 9.625", 36#, J-55 (or equiv.), ST&C casing to be set at ± 2252 ' in 12.25" hole.

LEAD:

±222 sx of Premium Plus V Blend. (Type V/Poz/Gel) or equivalent, with dispersant, fluid loss, accelerator, & LCM mixed at 11.0 ppg, 3.82 ft³/sk, 22.95 gal wtr/sx.

TAIL:

350 sx Class G or equivalent cement with bonding additive, LCM, dispersant, & fluid loss mixed at 15.6 ppg, 1.2 cuft/sx

Total estimated slurry volume for the 9.625" surface casing is 1268.4 ft³. Slurry includes 75% excess of calculated open hole annular volume to 2252'.

B. Production: 5.5", 17#, N-80 (or equiv.), LT&C casing to be set at ±8583' in 7.875" hole.

LEAD:

±260 sx of Premium Plus V Blend. (Type V/Poz/Gel) or equivalent, with dispersant, fluid loss, accelerator, & LCM mixed at 11.6 ppg, 3.10 ft³/sk, 17.71 gal wtr/sx.

TAIL:

400 sx Class G or equivalent cement with poz, bonding additive, LCM, dispersant, & fluid loss mixed at 13.0 ppg, 1.49 cuft/sx, 9.09 gal/sx.

Total estimated slurry volume for the 5.5" production casing is 1401.8 ft³. Slurry includes 15% excess of calculated open hole annular volume.

Note: The slurry design may change slightly based upon actual conditions. Final cement volumes will be determined from the caliper logs plus 15% or greater excess. The cement is designed to circulate on surface casing string. The production casing is designed for 1752' top of cement..

5. LOGGING PROGRAM:

- A. Mud Logger: The mud logger will come on at intermediate casing point and will remain on the hole until TD. The mud will be logged in 10' intervals.
- B. Open Hole Logs as follows: Run Array Induction/SFL/GR/SP fr/TD (8583') to the bottom of the surface csg. Run Neutron/Lithodensity/Pe/GR/Cal from TD (8583') to 2252'. Run Gamma Ray to surface.

6. FORMATION TOPS:

Please see attached directional plan.

7. ANTICIPATED OIL, GAS, & WATER ZONES:

A.

Formation	Expected Fluids	TV Depth Top
Green River	Water/Oil Shale	1,139
Mahogany Bench Mbr.	Water/Oil Shale	1,969
Wasatch Tongue	Oil/Gas/Water	4,057
Green River Tongue	Oil/Gas/Water	4,427
Wasatch*	Gas/Water	4,582
Chapita Wells*	Gas/Water	5,262
Uteland Buttes	Gas/Water	6,797
Mesaverde*	Gas/Water	7,662
Castlegate	Gas/Water	N/A

- B. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal isolation.
- C. There are no known potential sources of H₂S.

- D. The bottomhole pressure is anticipated to be between 4200 psi and 4600 psi.
- E. According to the USGS, the Base of Moderately Saline Water is at 4107'.

8. BOP EQUIPMENT:

Surface will utilize a 500 psi or greater diverter.

Production hole will be drilled with a 3000 psi BOP stack.

Minimum specifications for pressure control equipment are as follows:

Ram Type: 11" Hydraulic double ram with annular, 3000 psi w.p.

Ram type preventers and associated equipment shall be tested to stack working pressure if isolated by test plug or to 70% of internal yield pressure of casing. Pressure shall be maintained for at least 10 minutes or until requirements of test are met, whichever is longer. If a test plug is utilized, no bleed-off pressure is acceptable. For a test not utilizing a test plug, if a decline in pressure of more than 10% in 30 minutes occurs, the test shall be considered to have failed. Valve on casing head below test plug shall be open during test of BOP stack.

Annular type preventers (if used) shall be tested to 50% of rated working pressure. Pressure shall be maintained at least 10 minutes or until provisions of test are met, whichever is longer.

As a minimum, the above test shall be performed:

- a. when initially installed:
- b. whenever any seal subject to test pressure is broken
- c. following related repairs: and
- d. at 30 day intervals

Valves shall be tested from working pressure side during BOPE tests with all down stream valves open.

When testing the kill line valve(s) shall be held open or the ball removed.

Annular preventers (if used) shall be functionally operated at least weekly.

Pipe and blind rams shall be activated each trip, however, this function need not be performed more than once a day.

A BOPE pit level drill shall be conducted weekly for each drilling crew.

The BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No.2 for equipment and testing requirements, procedures, etc., and individual components shall be operable as designed. Chart recorders shall be used for all pressure tests. Pressure tests shall apply to all related well control equipment.

BOP systems shall be consistent with API RP53. Pressure tests will be conducted before drilling out from under casing strings which have been set and cemented in place. Test pressures for BOP equipment are as follows:

Annular BOP -- 1500 psi
Ram type BOP -- 3000 psi
Kill line valves -- 3000 psi
Choke line valves and choke manifold valves -- 3000 psi
Chokes -- 3000 psi
Casing, casinghead & weld -- 1500 psi
Upper kelly cock and safety valve -- 3000 psi
Dart valve -- 3000 psi

Blowout preventer controls will be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned. Preventers will be inspected and operated at least daily to ensure good mechanical working order, and this inspection will be recorded on the daily drilling report. Preventers will be pressure tested before drilling casing cement plugs.

The BLM in Vernal, UT shall be notified, at least 24 hours prior to initiating the pressure test, in order to have a BLM representative on location during pressure testing.

- a. The size and rating of the BOP stack is shown on the attached diagram.
- b. A choke line and a kill line are to be properly installed.
- c. The accumulator system shall have a pressure capacity to provide for repeated operation of hydraulic preventers.
- d. Drill string safety valve(s), to fit all tools in the drill string, are to be maintained on the rig floor while drilling operations are in progress.
- e. See attached BOP & Choke manifold diagrams.

9. COMPANY PERSONNEL:

<u>Name</u>	<u>Title</u>	Office Phone	Home Phone
John Egelston	Drilling Engineer	505-333-3163	505-330-6902
Bobby Jackson	Drilling Superintendent	505-333-3224	505-486-4706
Jeff Jackson	Project Geologist	817-885-2800	

SURFACE USE PLAN

Name of Operator:

XTO Energy, Inc.

Address:

PO Box 1360; 978 North Crescent Road

Roosevelt, Utah 84066

Well Location:

RBU 22-21E

Surface Location: 2,133' FSL & 1,975' FWL, NE/4 SW/4,

Target Location: 2,570' FNL & 1,650' FWL, SW/4 NE/4, SEN W

Section 21, T10S, R19E, SLB&M, Uintah County, Utah

The surface owner or surface owner representative and dirt contractor will be provided with an approved copy of the surface use plan of operations and approved conditions of approval before initiating construction.

The onsite inspection for the referenced well was conducted on Tuesday, April 29, 2008 at approximately 2:21 pm. In attendance at the onsite inspection were the following individuals:

BLM - Vernal Field Office Natural Resource Specialist Karl Wright BLM - Vernal Field Office Brandon McDonald Wildlife Biologist Inspector DOGM - Roosevelt Field Office Floyd Bartlett Uintah Engineering & Land Surveying Brandon Bowthorpe Surveyor Foreman Jackson Construction Randy Jackson LaRose Construction Billy McClure Foreman XTO Energy Inc. Jody Mecham Engineer Regulatory Coordinator XTO Energy, Inc. Ken Secrest

1. **Location of Existing Roads:**

- a. The proposed well site is located approximately 27.37 miles southwest of Ouray, Utah.
- b. Directions to the proposed well site have been attached at the end of Exhibit B.
- c. The use of roads under State and County Road Department maintenance are necessary to access the River Bend Unit area. However, an encroachment permit is not anticipated since no upgrades to the State or County Road system are proposed at this time.
- d. All existing roads will be maintained and kept in good repair during all phases of operation.
- e. Vehicle operators will obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions.
- Since no improvements are anticipated to the State, County, Tribal or BLM access roads no topsoil striping will occur.
- g. An off-lease federal Right-of-Way is not anticipated for the access road and utility corridors since both are located entirely within the River Bend Unit area.

2. Planned Access Roads:

 No new access is proposed since the well will be drilled from the existing RBU 11-21E utilizing the existing access road.

Location of Existing Wells:

a. Exhibit B has a map reflecting these wells within a one mile radius of the proposed well.

4. Location of Existing and/or Proposed Production Facilities:

- a. All permanent structures will be painted a flat, non-reflective Covert Green /Carlsbad Canyon to match the standard environmental colors. All facilities will be painted within six months of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.
- Site security guidelines identified in 43 CFR 3163.7-5 and Onshore Oil and Gas Order No. 3 will be adhered to.
- c. A gas meter run will be constructed and located on lease within 500 feet of the wellhead. Meter runs will be housed and/or fenced. All gas production and measurement shall comply with the provisions of 43 CFR 3162. 7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3.
- d. A tank battery will be constructed on this lease, it will be surrounded by a dike of sufficient capacity to contain the storage capacity of the largest tank. All loading lines and valves will be placed inside the berm surrounding the tank battery. All liquid hydrocarbons production and measurement shall conform to the provisions of 43 CFR 3162.7-3 and Onshore Oil and Gas Order No. 4 and Onshore Oil and Gas Order No. 5 for natural gas production and measurement.
- e. Any necessary pits will be properly fenced to prevent any wildlife and livestock entry.
- f. All access roads will be maintained as necessary to prevent erosion and accommodate year-round traffic. The road will be maintained in a safe useable condition.
- g. The site will require periodic maintenance to ensure that drainages are kept open and free of debris, ice, and snow, and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.
- h. No new pipeline is proposed since the well will be drilled from the existing RBU 11-21E utilizing the existing pipeline corridor.

Location and Type of Water Supply:

- a. No water supply pipelines will be laid for this well.
- b. No water well will be drilled for this well.
- c. Drilling water for this will be hauled on the road(s) shown in Exhibit B.
- d. Water will be hauled from one of the following sources:
 - Water Permit # 43-10991, Section 9, T8S, R20E;
 - Water Permit #43-2189, Section 33, T8S, R20E;
 - Water Permit #49-2158, Section 33, T8S, R20E;
 - Water Permit #49-2262, Section 33, T8S, R20E;

- Water Permit #49-1645, Section 5, T9S, R22E;
- Water Permit #43-9077, Section 32, T6S, R20E;
- Tribal Resolution 06-183, Section 22, T10S, R20E;

Source of Construction Material:

- a. The use of materials will conform to 43 CFR 3610.2-3.
- b. No construction materials will be removed from Ute Tribal or BLM lands.
- c. If any gravel is used, it will be obtained from a state approved gravel pit.

7. Methods of Handling Waste:

- All wastes associated with this application will be contained and disposed of utilizing approved facilities.
- b. Drill cuttings will be contained and buried on site.
- The reserve pit will be located outboard of the location and along the west side of the pad.
- d. The reserve pit will be constructed so as not to leak, break, or allow any discharge.
- e. The reserve pit will be lined with 16 mil minimum thickness plastic nylon reinforced liner material. The liner will overlay a felt liner pad only if rock is encountered during excavation. The pit liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. Pit walls will be sloped no greater than 2:1. A minimum 2-foot freeboard will be maintained in the pit at all times during the drilling and completion operation.
- f. The reserve pit has been located in cut material. Three sides of the reserve pit will be fenced before drilling starts. The fourth side will be fenced as soon as drilling is completed, and shall remain until the pit is dry. After the reserve pit has dried, all areas not needed for production will be rehabilitated.
- g. No chemicals subject to reporting under SARA Title III (hazardous materials) in an amount greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completion of the well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completion of the well.
- h. Trash will be contained in a trash cage and hauled away to an approved disposal site as necessary but no later than at the completion of drilling operations. The contents of the trash container will be hauled off periodically to the approved Uintah County Landfill near Vernal, Utah.
- Produced fluids from the well other than water will be produced into a test tank until such time as construction of production facilities is completed. Any spills of oil, gas, salt water or other produced fluids will be cleaned up and removed.
- j. After initial clean-up, a 400 bbl tank will be installed to contain produced waste water. This water will be transported from the tank to an approved XTO Energy, Inc. disposal well for disposal.

- k. Produced water from the production well will be disposed of at the RBU 13-11F or RBU 16-19F disposal wells in accordance with Onshore Order #7.
- I. Any salts and/or chemicals, which are an integral part of the drilling system, will be disposed of in the same manner as the drilling fluid.
- m. Sanitary facilities will be on site at all times during operations. Sewage will be placed in a portable chemical toilet and the toilet replaced periodically utilizing a licensed contractor to transport by truck the portable chemical toilet so that its contents can be delivered to the Vernal Wastewater Treatment Facility in accordance with state and county regulations.

8. Ancillary Facilities:

- a. Garbage Containers and Portable Toilets are the only ancillary facilities proposed in this application.
- b. No camps, airstrips or staging areas are proposed with this application.

9. Well Site Layout: (See Exhibit B)

- a. The well will be properly identified in accordance with 43 CFR 3162.6.
- b. Access to the well pad will be from the north.
- c. The pad and road designs are consistent with BLM specifications.
- d. A pre-construction meeting with responsible company representative, contractors and the BLM will be conducted at the project site prior to commencement of surface-disturbing activities. The pad and road will be construction-staked prior to this meeting.
- e. The pad has been staked at its maximum size; however it will be constructed smaller if possible, depending upon rig availability. Should the layout change, this application will be amended and approved utilizing a sundry notice.
- f. All surface disturbing activities, will be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.
- q. All cut and fill slopes will be such that stability can be maintained for the life of the activity.
- h. Diversion ditches will be constructed as shown around the well site to prevent surface waters form entering the well site area.
- The site surface will be graded to drain away from the pit to avoid pit spillage during large storm events.
- j. The stockpiled topsoil (first 6 inches or maximum available) will be stored in a windrow on the uphill side of the location to prevent any possible contamination. All topsoil will be stockpiled for reclamation in such a way as to prevent soil loss and contamination.
- k. Pits will remain fenced until site cleanup.
- I. The blooie line will be located at least 100 feet from the well head.
- m. Water injection may be implemented if necessary to minimize the amount of fugitive dust.

10. Plans for Restoration of the Surface (Interim Reclamation and Final Reclamation):

- a. Site reclamation for a producing well will be accomplished for portions of the site not required for the continued operation of the well.
- b. Upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1. Once the reserve pit is dry, the plastic nylon reinforced liner shall be torn and perforated before backfilling of the reserve pit. The reserve pit and that portion of the location not needed for production facilities/operations will be re-contoured to the approximate natural contours.
- c. Following BLM published Best Management Practices the interim reclamation will be completed within 90 days of completion of the well to reestablish vegetation, reduce dust and erosion and compliment the visual resources of the area.
 - a. All equipment and debris will be removed from the area proposed for interim reclamation and the pit area will be backfilled and re-contoured.
 - b. The area outside of the rig anchors and other disturbed areas not needed for the operation of the well will be re-contoured to blend with the surrounding area and reseeded at 12 lbs /acre with the following native grass seeds:

Hy-Crested Wheat Grass

(4 lbs / acre)

Needle and Thread Grass

(4 lbs / acre)

o Squirrel Tail

(4 lbs / acre)

- c. Reclaimed areas receiving incidental disturbance during the life of the producing well will be re-contoured and reseeded as soon as practical.
- d. The Operator will control noxious weeds along access road use authorizations, pipeline route authorizations, well sites, or other applicable facilities by spraying or mechanical removal. A list of noxious weeds may be obtained from the BLM or the appropriate County Extension Office. On BLM administered land, it is required that a Pesticide Use Proposal be submitted and approved prior to the application of herbicides, pesticides or possibly hazardous chemicals.
- e. Prior to final abandonment of the site, all disturbed areas, including the access road, will be scarified and left with a rough surface. The site will then be seeded and/or planted as prescribed by the BLM. The BLM recommended seed mix will be detailed within their approval documents.

11. Surface and Mineral Ownership:

- Surface Ownership Federal under the management of the Bureau of Land Management - Vernal Field Office, 170 South 500 East, Vernal, Utah 84078; 435-781-4400.
- Mineral Ownership Federal under the management of the Bureau of Land Management - Vernal Field Office, 170 South 500 East, Vernal, Utah 84078; 435-781-4400.

12. Other Information:

a. Operators Contact Information:

Title	Name	Office Phone	Mobile Phone	<u>e-mail</u> .
Company Rep. Agent	Ken Secrest Don Hamilton			Ken_Secrest@xtoenergy.com starpoint@etv.net

- b. An Independent Archeologist. has conducted a Class III archeological survey. A copy of the report is attached and has also been submitted under separate cover to the appropriate agencies by An Independent Archeologist.
- c. Alden Hamblin has conducted a paleontological survey. A copy of the report is attached and has also been submitted under separate cover to the appropriate agencies by Alden Hamblin.
- d. Our understanding of the results of the onsite inspection are:
 - No Threatened and Endangered flora and fauna species were found during the onsite inspection.
 - No drainage crossings that require additional State or Federal approval are being crossed.

Certification:

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exists; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application and that bond coverage is provided under XTO Energy, Inc's BLM bond UTB-000138. These statements are subject to the provisions of 18 U.S.C. 1001 for the fling of false statements.

Executed this 22nd day of September, 2008.

Don Hamilton -- Agent for XTO Energy, Inc.

2580 Creekview Road Moab, Utah 84532

435-719-2018 starpoint@etv.net





San Juan Division Drilling Department

Calculation Method: Minimum Curvature

Geodetic Datum: North American Datum 1983

Lat: 39° 55' 52.522 N Long: 109° 47' 22.790 W




Azimuths to True North Magnetic North: 11.52°

> Magnetic Field Strength: 52547.3nT Dip Angle: 65.83° Date: 9/16/2008 Model: IGRF200510

	ON TOP DETAILS			C/	ASING DETA	AILS	
4057.0 4140.2	Green River Mahogany Shale Wasatch Tongue Green River Tongue Wasatch Chapita Wells Uteland Buttes		2 8	2200.0 225 8500.0 858	MD 52.4 33.2	9 5/8" 5 1/2"	Size 9-5/8 5-1/2
7662.0 7745.2	Mesaverde				(150 ft/in)		
		5 1/2"	0 -2		2-21E Re	quested B	- - - - - - -
				9 5/8"		\$	-450 - - - - - - - - - - - - - - - - - - -
1000	9 5/8"	-					300
2000 3000			NO STATE OF THE PARTY OF THE PA	. `			225
r*000			-				150
5000							F
6000 1000							75
8000	5 1/2"						\ 0
9000							
10000	IN THE PERSON NAMED IN THE	&					

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	300.0	0.00	0.00	300.0	0.0	0.0	0.00	0.00	0.0	
3	785.9	14.58	330.68	780.7	53.6	-30.1	3.00	330.68	61.5	
4	3047.4	14.58	330.68	2969.3	549.8	-308.8	0.00	0.00	630.6	
5	3533.2	0.00	0.00	3450.0	603.4	-338.9	3.00	180.00		
6	4283.2	0.00	0.00	4200.0	603.4	-338.9	0.00	0.00	692.1	RBU 22-21E Requested BHL
7	8583.2	0.00	0.00	8500.0	603.4	-338.9	0.00	0.00	692.1	



Vertical Section at 330.68°

XTO Energy

Natural Buttes Wells(NAD83) RBU 22-21E RBU 22-21E RBU 22-21E

Plan: Permitted Wellbore

Standard Planning Report

16 September, 2008

Planning Report

Database:

EDM 2003.14 Single User Db

Company:

XTO Energy

Project:

Natural Buttes Wells(NAD83)

Site: Well: RBU 22-21E **RBU 22-21E**

Wellbore:

RBU 22-21E

Design:

Permitted Wellbore

Local Co-ordinate Reference:

TVD Reference:

MD Reference:

North Reference: **Survey Calculation Method:** Well RBU 22-21E

Rig KB @ 5202.0ft (Frontier #6) Rig KB @ 5202.0ft (Frontier #6)

Minimum Curvature

Project

Natural Buttes Wells(NAD83), Vernal, UT

Map System: Geo Datum:

US State Plane 1983

North American Datum 1983

System Datum:

Mean Sea Level

Using Well Reference Point

Map Zone:

Utah Northern Zone

Site

RBU 22-21E, T10S, R19E

Site Position:

Lat/Long

Northing:

 $3,139,058.41\,\mathrm{ft}$

Latitude:

39° 55' 52.522 N

From:

Easting: Slot Radius: 2,120,143.92ft

Longitude:

Position Uncertainty:

0.0 ft

109° 47' 22.790 W

Grid Convergence:

1.13 °

Well

RBU 22-21E, S-Well to Wasatch/Mesaverde

Well Position

+N/-S +E/-W

0.0 ft 0.0 ft Northing: Easting:

3,139,058.41 ft 2,120,143.92 ft Latitude: Longitude:

39° 55' 52.522 N 109° 47' 22.790 W

Position Uncertainty

0.0 ft

Wellhead Elevation:

5,188.0 ft

Ground Level:

5,188.0 ft

Wellbore

RBU 22-21E

Magnetics

Model Name

Sample Date

Declination (°)

Dip Angle (°)

Field Strength

(nT)

IGRF200510

9/16/2008

11.52

65.83

52,547

Design

Permitted Wellbore

Audit Notes:

Version:

Phase:

PROTOTYPE

Tie On Depth:

0,0

+N/-S

+E/-W

Vertical Section:

Depth From (TVD) (ft)

0.0

(ft) 0.0

(ft) 0.0 Direction (°) 330.68

lan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.00	0.00	0.00	0.00	
785.9	14.58	330.68	780.7	53.6	-30.1	3.00	3.00	0.00	330.68	
3,047.4	14.58	330.68	2,969.3	549.8	-308.8	0.00	0.00	0.00	0.00	
3,533.2	0.00	0.00	3,450.0	603.4	-338.9	3.00	-3.00	0.00	180.00	
4,283.2	0.00	0.00	4,200.0	603.4	-338.9	0.00	0.00	0.00	0.00	RBU 22-21E Requ
8,583.2	0.00	0.00	8,500.0	603.4	-338.9	0.00	0.00	0.00	0.00	

Planning Report

Database:

EDM 2003.14 Single User Db

Company:

XTO Energy

Project: Site: Natural Buttes Wells(NAD83) RBU 22-21E

Well:

RBU 22-21E

Wellbore: Design: RBU 22-21E Permitted Wellbore Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

Survey Calculation Method:

Well RBU 22-21E

Rig KB @ 5202.0ft (Frontier #6) Rig KB @ 5202.0ft (Frontier #6)

True

Minimum Curvature

	Measured			Vertical			Vertical	Dogleg	Build	Tum
(N) (P) (R) (R) (R) (R) (P100R)		Inclination	Azimuth		+N/-S	+E/-W	Section	Rate	Rate	Rate
10 0 0.00 0.00 0.00 0.00 0.00 0.00 0.00										
100.0	0.0			0.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0										0.00
300.0										
\$\frac{400.0}{500.0}										
Social Color										0.00
800.0 9.00 330.88 598.8 20.5 -11.5 22.5 3.00 3.00 0.00 770.0 12.00 330.88 598.8 70.7 53.6 -20.4 41.7 3.00 3.00 0.00 785.9 14.58 330.88 790.7 53.6 -30.1 61.5 3.00 3.00 0.00 800.0 14.58 330.88 891.1 78.6 -44.2 90.2 0.00 0.00 0.00 1.000.0 14.58 330.88 987.9 100.6 -59.5 115.4 0.00 0.00 0.00 1.100.0 14.58 330.88 1.189.0 134.8 -75.7 154.7 0.00 0.00 0.00 1.100.0 14.58 330.88 1.189.0 134.8 -75.7 154.7 0.00 0.00 0.00 1.100.0 14.58 330.88 1.181.4 144.5 -81.1 165.7 0.00 0.00 0.00 1.200.0 14.58 330.88 1.181.4 144.5 -81.1 165.7 0.00 0.00 0.00 1.300.0 14.58 330.88 1.375.0 188.4 -105.8 216.0 0.00 0.00 0.00 1.400.0 14.58 330.88 1.375.0 188.4 -105.8 216.0 0.00 0.00 0.00 1.500.0 14.58 330.88 1.59.6 222.2 -130.4 266.4 0.00 0.00 0.00 1.500.0 14.58 330.88 1.596.6 222.2 -130.4 266.4 0.00 0.00 0.00 1.700.0 14.58 330.88 1.585.4 224.2 -142.8 291.5 0.00 0.00 0.00 1.800.0 14.58 330.88 1.886.9 296.1 -167.4 341.9 0.00 0.00 0.00 1.800.0 14.58 330.88 1.886.9 296.1 -167.4 341.9 0.00 0.00 0.00 1.900.0 14.58 330.88 1.985.0 323.0 -181.4 370.5 0.00 0.00 0.00 2.000.0 14.58 330.88 1.985.0 323.0 -181.4 370.5 0.00 0.00 0.00 2.000.0 14.58 330.88 2.149.3 330.8 2.61.0 0.00 0.00 0.00 2.000.0 14.58 330.88 2.449.3 363.9 2.244 417.4 0.00 0.00 0.00 2.000.0 14.58 330.88 2.449.3 363.9 2.244 417.4 0.00 0.00 0.00 2.000.0 14.58 330.88 2.449.8 368.9 368.1 -167.4 341.9 0.00 0.00 0.00 2.000.0 14.58 330.88 2.449.8 368.8 2.449.6 368.8 2.449.6 0.00 0.00 0.00 0.00 2.000.0 14.58 330.88 2.449.8 368.8 2.449.6 0.00 0.00 0.00 0.00 2.000.0 14.58										
700.0 12.00 330.68 697.1 38.4 -20.4 417 3.00 3.00 0.00 765.9 14.58 330.68 780.7 53.6 -30.1 61.5 3.00 3.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00										
TSES										
800.0 14.58 330.68 794.3 56.7 -31.8 65.0 0.00 0.00 0.00 0.00 0.00 1,000.0 14.58 330.68 891.1 78.6 -44.2 90.2 0.00 0.00 0.00 0.00 1,100.0 14.58 330.68 1,084.7 122.5 -88.8 140.5 0.00 0.00 0.00 0.00 1,156.1 14.58 330.68 1,139.0 134.8 -75.7 154.7 0.00 0.00 0.00 0.00 1,156.1 14.58 330.68 1,139.0 134.8 -75.7 154.7 0.00 0.00 0.00 0.00 0.00 1,156.1 14.58 330.68 1,139.0 134.8 -75.7 164.7 0.00 0.00 0.00 0.00 1,100 0.00 1,156.1 14.58 330.68 1,139.0 134.8 -75.7 164.7 0.00 0.00 0.00 0.00 0.00 1,100 0.00 1,156.0 14.58 330.68 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 0.00 1,150.0 14.58 330.68 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 0.00 1,150.0 14.58 330.68 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 0.00 1,150.0 14.58 330.68 1,565.6 232.2 130.4 266.4 0.00 0.00 0.00 0.00 1,1700.0 14.58 330.68 1,685.4 254.2 130.4 266.4 0.00 0.00 0.00 0.00 1,1700.0 14.58 330.68 1,685.4 254.2 130.4 266.4 0.00 0.00 0.00 0.00 1,1700.0 14.58 330.68 1,685.8 254.2 130.4 266.4 0.00 0.00 0.00 0.00 1,1700.0 14.58 330.68 1,685.9 298.1 1-67.4 341.9 0.00 0.00 0.00 0.00 1,1500 0.0 14.58 330.68 1,855.7 320.0 145.4 341.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0										
900.0 14.58 330.68 987.9 100.6 -56.5 115.4 0.00 0.00 0.00 1.100.0 14.58 330.68 1.084.7 122.5 -68.8 140.5 0.00 0.00 0.00 0.00 1.156.1 14.58 330.68 1.084.7 122.5 -68.8 140.5 0.00 0.00 0.00 0.00 1.156.1 14.58 330.68 1.084.7 122.5 -68.8 140.5 0.00 0.00 0.00 0.00 1.156.1 14.58 330.68 1.139.0 134.8 -75.7 154.7 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0										0.00
1,000.0	800.0	14.58	330.68	794.3	56.7	-31.8	65.0	0.00	0.00	0.00
1,100.0 14.58 330.68 1,138.0 134.8 -75.7 154.7 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	900.0	14.58	330.68	891.1	78.6	-44.2	90.2	0.00		0.00
1,166.1	1,000.0	14.58	330.68	987.9	100.6	-56.5				0.00
1,166.1	1,100.0	14.58	330.68	1,084.7	122.5	-68.8	140.5	0.00	0.00	0.00
1,200.0				•		-75.7	154.7	0.00	0.00	0.00
1,300.0 14.58 330.68 1,278.2 166.4 -93.5 190.9 0.00 0.00 0.00 1,4600 14.58 330.68 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 0.01 1,500.0 14.58 330.68 1,471.8 210.3 -118.1 241.2 0.00 0.00 0.00 0.01 1,500.0 14.58 330.68 1,566.6 232.2 -130.4 266.4 0.00 0.00 0.00 0.01 1,700.0 14.58 330.68 1,665.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.01 1,500.0 14.58 330.68 1,665.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,665.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,858.9 298.1 -167.4 341.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0										
1,400.0 14.58 330.88 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 1.500.0 14.58 330.88 1,471.8 210.3 -118.1 241.2 0.00 0.00 0.00 0.00 1.500.0 14.58 330.88 1,568.6 232.2 -130.4 268.4 0.00 0.00 0.00 0.00 1.700.0 14.58 330.88 1,686.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1.500.0 14.58 330.88 1,686.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1.500.0 14.58 330.88 1,858.9 298.1 -167.4 341.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0	1,200.0	14.58	330.68	1,181.4	144.5	-81.1	165.7	0.00	0.00	0.00
1,400.0 14.58 330.68 1,375.0 188.4 -105.8 216.0 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,575.6 232.2 -130.4 266.4 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,556.6 232.2 -130.4 266.4 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,565.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,556.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1,500.0 14.58 330.68 1,556.7 320.0 -157.4 341.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0	1,300.0	14.58	330.68	1,278.2	166.4	-93.5	190.9	0.00	0.00	0.00
1,500.0	•		330.68	•	188.4	-105.8	216.0	0.00	0.00	0.00
1,600.0	,				210.3	-118.1	241.2	0.00	0.00	0.00
1,700.0 14.58 330.68 1,665.4 254.2 -142.8 291.5 0.00 0.00 0.00 0.00 1,800.0 14.58 330.68 1,762.1 276.1 -155.1 316.7 0.00 0.00 0.00 0.00 1,900.0 14.58 330.68 1,858.9 298.1 -167.4 341.9 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0				•					0.00	0.00
1,800.0 14,58 330.68 1,762.1 276.1 -155.1 316.7 0.00 0.00 0.00 1,190.0 14,58 330.68 1,858.9 298.1 -167.4 341.9 0.00 0.00 0.00 0.00 2,001.3 7 14,58 330.68 1,968.0 323.0 -181.4 370.5 0.00 0.00 0.00 0.00 0.00 0.00 0.00				•						0.00
1,900.0 14.58 330.68 1,858.9 298.1 -167.4 341.9 0.00 0.00 0.00 0.00 2,013.7 14.58 330.68 1,955.7 320.0 -179.7 367.0 0.00 0.00 0.00 0.00 0.00 0.00 0.00		1/1 58	330 68	1 762 1	276.1	-155 1	316.7	0.00	0.00	0.00
2,000.0 14.58 330.68 1,955.7 320.0 -179.7 367.0 0.00 0.00 0.00 0.00 2,013.7 14.58 330.68 1,959.0 323.0 -181.4 370.5 0.00 0.00 0.00 0.00 0.00 0.00 0.00				•						
2,013.7 14.58 330.68 1,869.0 323.0 -181.4 370.5 0.00 0.00 0.00 0.00 Mahogany Shale 2,100.0 14.58 330.68 2,052.5 342.0 -192.1 392.2 0.00 0.00 0.00 0.00 0.00 2,252.4 14.58 330.68 2,200.0 375.4 -210.8 430.6 0.00 0.00 0.00 0.00 0.00 2,252.4 14.58 330.68 2,200.0 375.4 -210.8 430.6 0.00 0.00 0.00 0.00 0.00 0.00 0.00										
Mahogany Shale 2,100.0 14.58 330.68 2,052.5 342.0 -192.1 392.2 0.00 0.00 0.00 2,200.0 14.58 330.68 2,149.3 363.9 -204.4 417.4 0.00 0.00 0.00 9 5/8" 2,252.4 14.58 330.68 2,246.0 385.8 -216.7 442.5 0.00 0.00 0.00 2,300.0 14.58 330.68 2,246.0 385.8 -216.7 442.5 0.00 0.00 0.00 2,400.0 14.58 330.68 2,342.8 407.8 -229.0 467.7 0.00 0.00 0.00 2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,900.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00<	•									
2,100.0 14.58 330.68 2,149.3 363.9 -204.4 417.4 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0	•		330.06	1,909.0	323.0	-101.4	370.3	0.00	0.00	0.00
2,200.0			330 68	2 052 5	342 0	-192.1	392.2	0.00	0.00	0.00
2,252.4 14.58 330.68 2,200.0 375.4 -210.8 430.6 0.00 0.00 0.00 95/8" 2,300.0 14.58 330.68 2,246.0 385.8 -216.7 442.5 0.00 0.00 0.00 2,400.0 14.58 330.68 2,342.8 407.8 -229.0 467.7 0.00 0.00 0.00 2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,600.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.0 3,000.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.0 <tr< td=""><td>•</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr<>	•									
9 6/8" 2,300.0 14.58 330.68 2,246.0 385.8 -216.7 442.5 0.00 0.00 0.00 2,400.0 14.58 330.68 2,342.8 407.8 -229.0 467.7 0.00 0.00 0.00 2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.00 3,000.0 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.00				•						
2,300.0 14.58 330.68 2,246.0 385.8 -216.7 442.5 0.00 0.00 0.00 2,400.0 14.58 330.68 2,342.8 407.8 -229.0 467.7 0.00 0.00 0.00 2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.00 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.00 3,047.4		14.58	330.68	2,200.0	3/5.4	-210.8	430.0	0.00	0.00	0.00
2,400.0 14.58 330.68 2,342.8 407.8 -229.0 467.7 0.00 0.00 0.00 2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.00 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 3,200.0 10.00 330										
2,500.0 14.58 330.68 2,439.6 429.7 -241.3 492.9 0.00 0.00 0.00 2,600.0 14.58 330.68 2,536.4 451.7 -253.7 518.0 0.00 0.00 0.00 2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.00 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.00 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.00 3,000.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0	2,300.0			•						0.00
2,600.0	2,400.0	14.58	330.68	2,342.8	407.8	-229.0				0.00
2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.0 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.0 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.0 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.0 3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,400.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,500.0	2,500.0	14.58	330.68	2,439.6	429.7	-241.3	492.9	0.00	0.00	0.00
2,700.0 14.58 330.68 2,633.2 473.6 -266.0 543.2 0.00 0.00 0.00 2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.0 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.0 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.0 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.0 3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,500.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,500.0	2,600.0	14.58	330.68	2,536.4	451.7	-253.7	518.0	0.00		0.00
2,800.0 14.58 330.68 2,729.9 495.6 -278.3 568.4 0.00 0.00 0.00 2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.0 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.0 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.0 3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,400.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,500.0	2,700.0	14.58	330.68	2,633.2	473.6	-266.0	543.2	0.00	0.00	0.00
2,900.0 14.58 330.68 2,826.7 517.5 -290.6 593.5 0.00 0.00 0.00 3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.00 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.00 3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,500.0 <td>•</td> <td>14.58</td> <td>330.68</td> <td>2,729.9</td> <td>495.6</td> <td>-278.3</td> <td>568.4</td> <td>0.00</td> <td>0.00</td> <td>0.00</td>	•	14.58	330.68	2,729.9	495.6	-278.3	568.4	0.00	0.00	0.00
3,000.0 14.58 330.68 2,923.5 539.4 -303.0 618.7 0.00 0.00 0.00 3,047.4 14.58 330.68 2,969.3 549.8 -308.8 630.6 0.00 0.00 0.00 3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00		14.58	330.68	2,826.7	517.5	-290.6	593.5	0.00	0.00	0.00
3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0							618.7	0.00	0.00	0.00
3,100.0 13.00 330.68 3,020.5 560.8 -314.9 643.2 3.00 -3.00 0.0 3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.0	3.047.4	14.58	330.68	2,969.3	549.8	-308.8	630.6	0.00	0.00	0.00
3,200.0 10.00 330.68 3,118.5 578.1 -324.7 663.1 3.00 -3.00 0.0 3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -388.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 <td></td> <td></td> <td></td> <td>,</td> <td></td> <td></td> <td></td> <td></td> <td>-3.00</td> <td>0.00</td>				,					-3.00	0.00
3,300.0 7.00 330.68 3,217.3 591.0 -331.9 677.9 3.00 -3.00 0.0 3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -388.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00										0.00
3,400.0 4.00 330.68 3,316.9 599.4 -336.6 687.4 3.00 -3.00 0.0 3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 <td></td> <td></td> <td></td> <td>•</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0.00</td>				•						0.00
3,500.0 1.00 330.68 3,416.8 603.2 -338.8 691.8 3.00 -3.00 0.0 3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0										0.00
3,533.2 0.00 0.00 3,450.0 603.4 -338.9 692.1 3.00 -3.00 0.0 3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.00 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.00 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0				•						0.00
3,600.0 0.00 0.00 3,516.8 603.4 -338.9 692.1 0.00 0.00 0.00 3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.00 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.00 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.00 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.00				,						0.00
3,700.0 0.00 0.00 3,616.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.0 3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0	,									0.00
3,800.0 0.00 0.00 3,716.8 603.4 -338.9 692.1 0.00 0.00 0.00 0.0 0.0 0.0 0.0 0.0 0.										0.00
3,900.0 0.00 0.00 3,816.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0	•									
4,000.0 0.00 0.00 3,916.8 603.4 -338.9 692.1 0.00 0.00 0.0 4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0	3,800.0									
4,100.0 0.00 0.00 4,016.8 603.4 -338.9 692.1 0.00 0.00 0.0				•						0.00
4,100.0										
4,140.2 0.00 0.00 4,057.0 603.4 -338.9 692.1 0.00 0.00 0.0									0.00 0.00	0.00 0.00

Planning Report

Database:

EDM 2003.14 Single User Db

Company:

XTO Energy

Project: Site: Natural Buttes Wells(NAD83) RBU 22-21E

Well:

RBU 22-21E

Wellbore: Design: RBU 22-21E Permitted Wellbore Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference: Survey Calculation Method: Well RBU 22-21E

Rig KB @ 5202.0ft (Frontier #6) Rig KB @ 5202.0ft (Frontier #6)

True

Minimum Curvature

Measured			Vertical			Vertical	Dogleg	Build	Turn
Depth (ft)	Inclination (°)	Azimuth (°)	Depth (ft)	+N/-S (ft)	+E/-W (ft)	Section (ft)	Rate (°/100ft)	Rate (°/100ft)	Rate (°/100ft)
4,200.0	0.00	0.00	4,116.8	603.4	-338.9	692.1	0.00	0.00	0.00
4,283.2	0.00	0.00	4,200.0	603.4	-338.9	692.1	0.00	0.00	0.00
RBU 22-21E	Requested Bi	HL							
4,300.0	0.00	0.00	4,216.8	603.4	-338.9	692.1	0.00	0.00	0.00
4,400.0	0.00	0.00	4,316.8	603.4	-338.9	692.1	0.00	0.00	0.00
4,500.0	0.00	0.00	4,416.8	603.4	-338.9	692.1	0.00	0.00	0.00
4,510.2	0.00	0.00	4,427.0	603.4	-338.9	692.1	0.00	0.00	0.00
Green River	Tongue								
4,600.0	0.00	0.00	4,516.8	603.4	-338.9	692.1	0.00	0.00	0.00
4,665.2	0.00	0.00	4,582.0	603.4	-338.9	692.1	0.00	0,00	0.00
	0.00	0.00	4,002.0	000.1	000.0	302.1	0.00	5,55	5,55
Wasatch	0.00	0.00	A 616 0	603.4	-338.9	692.1	0.00	0.00	0.00
4,700.0	0.00		4,616.8		-336.9 -338.9	692.1	0.00	0.00	0.00
4,800.0	0.00	0.00	4,716.8	603.4 603.4	-338.9 -338.9	692.1	0.00	0.00	0.00
4,900.0	0.00	0.00	4,816.8	003.4	-ააი.ყ	092.1	0.00		
5,000.0	0.00	0.00	4,916.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,100.0	0.00	0.00	5,016.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,200.0	0.00	0.00	5,116.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,300.0	0.00	0.00	5,216.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,345.2	0.00	0.00	5,262.0	603.4	-338.9	692.1	0.00	0.00	0.00
Chapita Wells	s								
5,400.0	0.00	0.00	5,316.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,500.0	0.00	0.00	5,416.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,600.0	0.00	0.00	5,516.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,700.0	0.00	0.00	5,616.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,800.0	0.00	0.00	5,716.8	603.4	-338.9	692.1	0.00	0.00	0.00
5,900.0	0.00	0.00	5,816.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,000.0	0.00	0.00	5,916.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,100.0	0.00	0.00	6,016.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,200.0	0.00	0.00	6,116.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,300.0	0.00	0.00	6,216.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,400.0	0.00	0.00	6,316.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,500.0	0.00	0.00	6,416.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,600.0	0.00	0.00	6,516.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,700.0	0.00	0.00	6,616.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,800.0	0.00	0.00	6,716.8	603.4	-338.9	692.1	0.00	0.00	0.00
6,880.2	0.00	0.00	6,797.0	603.4	-338.9	692.1	0.00	0.00	0.00
Uteland Butte	es								
6,900.0	0.00	0.00	6,816.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,000.0	0.00	0.00	6,916.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,100.0	0.00	0.00	7,016.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,200.0	0.00	0.00	7,116.8	603.4	-338.9	692.1	0,00	0.00	0.00
7,300.0	0.00	0.00	7,216.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,400.0	0.00	0.00	7,316.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,500.0	0.00	0.00	7,416.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,600.0	0.00	0.00	7,516.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,700.0	0.00	0.00	7,616.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,745.2	0.00	0.00	7,662.0	603.4	-338.9	692.1	0.00	0.00	0.00
Mesaverde			-						
7,800.0	0.00	0.00	7,716.8	603.4	-338.9	692.1	0.00	0.00	0.00
7,900.0	0.00	0.00	7,816.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,000.0	0.00	0.00	7,916.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,100.0	0.00	0.00	8,016.8	603.4	-338.9	692.1	0.00	0.00	0.00

Planning Report

Database:

EDM 2003.14 Single User Db

Company: Project:

XTO Energy

Natural Buttes Wells(NAD83)

Site: Well: RBU 22-21E RBU 22-21E

Wellbore: Design:

RBU 22-21E Permitted Wellbore

Local Co-ordinate Reference:

TVD Reference:

MD Reference:

North Reference: Survey Calculation Method: Well RBU 22-21E

Rig KB @ 5202.0ft (Frontier #6) Rig KB @ 5202.0ft (Frontier #6)


Minimum Curvature

d Survey									
Measured Depth (ft)	inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
8,200.0	0.00	0.00	8,116.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,300.0	0.00	0.00	8,216.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,400.0	0.00	0.00	8,316.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,500.0	0.00	0.00	8,416.8	603.4	-338.9	692.1	0.00	0.00	0.00
8,583.2	0.00	0.00	8,500.0	603.4	-338.9	692.1	0.00	0.00	0.00
5 1/2"									

Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
RBU 22-21E Requeste - plan hits target - Circle (radius 30.0)	0.00	0.00	4,200.0	603.4	-338.9	3,139,655.06	2,119,793.20	39° 55' 58.484 N	109° 47' 27.140 W

Casing Points							
	Measured Depth	Vertical Depth			Casing Diameter	Hole Diameter	
	(ft)	(ft)		Name	(")	(")	
	2,252.4	2,200.0	9 5/8"		9-5/8	12-1/4	
-	8,583.2	8,500.0	5 1/2"		5-1/2	7-7/8	

ormations						
	Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
	1,156.1	1,139.0	Green River		0.00	
	2,013.7	1,969.0	Mahogany Shale		0.00	
	4,140.2	4,057.0	Wasatch Tongue		0.00	
	4,510.2	4,427.0	Green River Tongue		0.00	
	4,665.2	4,582.0	Wasatch		0.00	
	5,345.2	5,262.0	Chapita Wells		0.00	
	6,880.2	6,797.0	Uteland Buttes		0.00	
	7,745.2	7,662.0	Mesaverde		0.00	



XTO Energy Corporation; River Bend Unit #22-21E: A Cultural Resource Inventory for a well its access and pipeline, Uintah County, Utah.

By James A. Truesdale

James A. Truesdale Principal Investigator

Prepared For XTO Energy Corporation 1400 North State Street P.O.Box 1360 Roosevelt, Utah 84066

Prepared By
AN INDEPENDENT ARCHAEOLOGIST
P.O.Box 153
Laramie, Wyoming
82073

Utah Project # U-08-AY-171(b)

April 18, 2008

Table of Contents

Table of Content	ts	-	-	-	-	_	-	-	-	-	-	-	-	-	-	-	-	-	-	-	i
List of Figures	-	-	-	-	-	-		-	-	-	-	-	-	_	_	-	_	_	_	-	ii
Introduction	-	-	-	-	_	-	-	-	-	-	_	_	-	_			-	-	-	_	1
File Search	-	_	_	_	-	-	-	-	-	_	_	-	-	_	-	-	-	-	-	-	1
Environment	-	-	-	-	-	-	-	-	_		-	_	-	-	_	-	-	-	_	_	1
River Bend Unit	#2	22-	-21	LΕ	-	-	-	-	-	-	-	-	_	-	-	_	-	-	-	-	4
Field Methods	-	_	-		_	-	_	-	-	_	-	-		-	-	-	_	-	-	-	5
Results	-	-	-	-	_	-	-	-	-	-	-	-	-	-	-	_		_	-	-	6
Recommendations	-	-	-	-	-	_	_	_	-	-	_	-	-	_	-	-	-	-	_	_	6
References Cited	ł	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	8

List of Figures

Figure	1.	Location of the XTO Energy Corporation proposed River Bend Unit (RBU) #22-21E well, its access and pipeline on 7.5'/1968 USGS quadrangle maps Moon Bottom, Uintah County, Utah 2
Figure	2.	View to southwest of the proposed RBU #22-21E centerstake located on the existing RBU #11-21EX well pad

Introduction

An Independent Archaeologist (AIA) was contacted by a representative of XTO Energy Corporation to conduct a cultural resources investigation of the proposed River Bend Unit (RBU) #22-21E well, its access and pipeline. The location of the project area is the NE/SW 1/4 of Section 21, T10S, R19E Uintah County, Utah (Figure 1).

The proposed RBU #22-21E well's centerstake footage (Alternate #1) is 2133' FSL, 1975' FWL. The proposed RBU #22-21E well's centerstake Universal Transverse Mercator (UTM) coordinate is Zone 12, North American Datum (NAD) 83, 06/03/417.71 mE 44/20/829.33 mN.

The proposed RBU #22-21E well will be directionally drilled from the existing RBU #11-21EX well pad. Therefore, the proposed RBU #22-21E well's access and pipeline is the existing access and pipeline associated with the RBU #11-21EX well.

The surface and minerals of Section 21 T10S R19E is administered by the U.S. Utah Bureau of Land Management (BLM), Vernal District Office, Book Cliffs Resource Area. A total of 10.0 acres (10 block, 0.0 linear) was surveyed. The fieldwork was conducted on April 9, 2008 by AIA owner and principal investigator James Truesdale. All the field notes and maps are located in the AIA office in Laramie, Wyoming.

File Search

A file search was conducted by the Office of the Utah Division of State History (UDSH), Antiquities Section, Records Division on March 27, 2008. An additional file search was conducted at the Vernal BLM office in March of 2006 by the author. An update of AIA's USGS 7.5'/1985 Moon Bottom quadrangle map from the UDSH's Moon bottom quadrangle base map occurred on November 8, 2003 and again on February 3, 2004. The UDSH SHPO GIS file search reported that twenty projects (U-00-AY-803, U-01-AY-123, U-02-AY-560, U-03-AY-210, U-03-AY-206, U-03-AY-209, U-03-AY-104, U-03-AY-341, U-03-AY-369, U-03-AY-379,U-04-AY-084, U-04-AY-085, U-08-AY-915, U-04-AY-916, U-04-AY-892, U-04-AY-893, U-04-AY-890, U-04-AY-995, U-05-AY-538 and U-06-AY-1166) have been previously conducted in the general area (Section 21 of T10S R19E). The Utah SHPO GIS files search indicated that no sites have been previously recorded in Section 21 of T10S R19E.

Environment

Physiographically, the project is located in the western part of the River Bend Unit on Wild Horse Bench in the Uinta Basin, 18 miles south of Ouray, Utah. The Uinta Basin is structurally the lowest part of the Colorado Plateau geographical province (Thornbury 1965:425).




Figure 1. Location of the XTO Energy Inc. proposed RBU #22-21E well on USGS 7.5' Quadrangle map Big Pack Mountain NW (1968).

The Uinta basin is a large, relatively flat, bowl shaped, east-west asymmetrical syncline near the base of the Uinta Mountains. The topography is characteristic of sloping surfaces that incline northward and are mainly dip slopes on the harder layers of Green River and Uinta Formations (Stokes 1986).

A thick section of more than 9000 feet (2743.9 m) of early Tertiary rocks are exposed (Childs 1950). These rocks are mainly Paleocene and Eocene in age and consist of sandstone, clay and shale lacustrine, fluviatile, and deltaic continental deposits, most famous of which are the lacustrine Green River Beds.

The immediate project area is situated on Wild Horse Bench that consists of a sequence of large upland hills and ridges that are located west of the Hill Creek Canyon and east of the Green River. The area is characterized as having steep ridges and/or buttes of relatively thick Uinta Formation sandstone, with thinner layers of clays and shale. The hills, ridges and buttes are dissected by several steep sided ephemeral drainage washes with wide flat alluvial plains. Portions of the desert hardpan and bedrock are covered with various sizes of residual angular to tabular pieces of eroding sandstone, clay and shale. Many of the higher hills and ridges exhibit ancient terrace (pediment) surfaces containing pebble and cobble gravel. Some of these pebbles and cobbles exhibit a dark brown to black desert varnish In addition, many of the hills and ridge slopes (patination). are covered with aeolian sand that may reach a depth of 100 to 150 cm.

Vegetation in the River Bend Unit area is characteristic of a low sagebrush community with shad scale and greasewood. Species observed in the project area include; big sagebrush (Artemesia tridentata), shadscale (Atriplex confertifolia), (Atriplex nuttallii), rabbitbrush (Chrysothamnus viscidiflorus), winterfat (Eurotia lanata), greasewood (Sarcobatus baileyi), wild buckwheat, Erigonum ovvalifolium), desert trumpet (Erigonum Indian rice grass (Oryzopsis hymenoides), western inflatum), wheatgrass (Agropyron smithii), spiked wheatgrass (Agropyron sp.), crested wheatgrass (Agropyron cristatum), June grass (Koeleria cristata), cheat grass (Bromus tectorum), desert globemallow (Bromus tectorum), lupine (Lupinus sp.), larkspur (Delphinium Indian paintbrush (Castilleja chromosa), peppergrass phacelia perfoliatum), scalloped (Phacelia intergrifolian), birdscage evening primrose (Oenothera Russian thistle (Salsola kali), Russian knapweed deltoides), (Centaurea repens), and prickly pear cactus (Opuntia sp.). addition, a riparian community dominated by tall greasewood, cottonwood (Populas sp.), willow (Salix sp.), and salt cedar (tamerix) can be found along the Hill Creek Canyon and Green River bottom.

River Bend Unit (RBU) #22-21E

The proposed RBU #22-21E well will be directionally drilled from the existing RBU #11-21EX well pad. The proposed RBU #22-21E well centerstake (2133' FSL, 1975 FWL) east existing RBU #11-21EX well head (Figure 2).




Figure 2. View to the east of the proposed RBU #22-21E well centerstake located on the existing RBU #11-21EX well pad.

The proposed RBU #22-21E well pad is situated along the edge and southern end of a large flat bench (Figure 2). This location is situated on Wild Horse Bench that is part of a much larger upland bench system of hills and ridges, and drainages that drain west to the Green River and east to the Hill and Willow Creek Sediments on the well location have been partially canyons. disturbed by the RBU #11-21EX well's construction. undisturbed sediments around the existing RBU #11-21EX well are colluvial in nature. These colluvial deposits consist of shallow (< 5 cm), tan to light brown, poorly sorted, moderately compacted, sandy clay loam, mixed with small to medium sized flat angular pieces of sandstone, clay and shale on the ridge. Exposed and eroding to light brown sandstone and shale bedrock dominate the well pad landscape. Vegetation consists of low sagebrush, saltbush, rabbitbrush, greasewood, bunchgrasses (wheatgrass, cheat grass, Indian rice-grass), barrel and prickly pear cactus. The proposed well location is 5251 feet (1600.91 m) AMSL.

As mentioned above, the proposed RBU #22-21E well will be directionally drilled from the existing RBU #11-21EX well pad. Therefore, the proposed access and pipeline for the RBU #22-21E well is the existing access and pipeline associated with the RBU #11-21EX well pad.

Field Methods

A total of 10 acres was surveyed around the centerstake of the proposed RBU #22-21E well location to allow for relocation of the pad if necessary. The survey was accomplished by walking transects spaced no more than 15 meters apart. As mentioned earlier, the proposed RBU #22-21E well will be directionally drilled from the existing RBU #11-21EX well pad. Therefore, the proposed access and pipeline are the existing access and pipeline associated with the RBU #11-21EX well. Thus, a total 0.0 linear acres was surveyed.

Geologic landforms (rockshelters, alcoves, ridge tops and saddles) and areas of subsurface exposure (ant hills, blowouts, rodent holes and burrow, eroding slopes and cutbanks) were examined with special care in order to locate cultural resources (sites, isolates) and possibly help assess a site's sedimentary integrity and potential for the presence and/or absence of buried intact cultural deposits. All exposures of sandstone cliff faces, alcoves or rockshelters, and talus slopes were surveyed.

When cultural materials are discovered, a more thorough survey of the immediate vicinity is conducted in order to locate any associated artifacts and to determine the horizontal extent (surface area) of the site. If no other artifacts are located during the search then the initial artifact was recorded as an isolated find. At times, isolated formal tools (typical end scrapers, projectile points) were drawn and measured. The isolate was then described and its location plotted on a U.S.G.S. topographic map and UTM coordinates are recorded.

When sites are found an Intermountain Antiquities Computer System (IMACS) form was used to record the site. At all sites, selected topographic features, site boundaries, stone tools and cultural features (hearths, foundations, trash dumps and trails) are mapped. Sites were mapped with a Brunton compass, Trimble Geophysical 3 and/or Garmin E-Trex GPS units, and pacing off distances from a mapping station (datum, PVC with aluminum tag). All debitage is inventoried using standard recording techniques (Truesdale et al 1995:7) according to material type, basic flake type, and so on. Selected (mostly complete) stone tools and projectile points are drawn and measured. All features (rockart panel(s), hearths, foundations, trash dumps and trails) are measured and described, while selected features are either drawn

or photographed.

Site location data is recorded by a Trimble GeoExplorer 3 Global Positioning System (GPS) and/or Garmin GPS III Plus or a E-Trex GPS. Site elevation and Universal Transverse Mercator (UTM) grid data, its Estimated Position Error (EPE) and Dilution of Precision (DOP) were recorded. Using the GPS data, the site location was then placed on a USGS 7.5' quadrangle map.

Results

A total of 10.0 (10 block, 0.0 linear) acres were surveyed for cultural resources by AIA within and around the proposed XTO Energy Corporation River Bend Unit (RBU) #22-21E well, and along its access and pipeline. No cultural resources (sites, isolates) were recorded on or around the proposed RBU #22-21E or along its access and pipeline.

The proposed RBU #22-21E well will directionally drilled from the existing RBU #11-21EX well pad. Therefore, the proposed access and pipeline is the access and pipeline associated with the RBU #11-21EX well pad.

A moderate scatter of modern trash (plastic bottles, sanitary food cans, miscellaneous metal, wire, green, brown and clear glass bottles and bottle fragments, foam insulation, etc.) can be found on and surrounding the existing well pads and along the existing oil and gas field service roads in the River Bend Unit area.

Recommendations

A total of 10.0 (10 block, 0.0 linear) acres were surveyed for cultural resources by AIA within and around the proposed XTO Energy Corporation River Bend Unit #22-21E well, and along its access and pipeline. No additional cultural resources (sites, isolates) were recorded on or around the proposed RBU #22-21E or along its access and pipeline.

As mentioned earlier, the proposed RBU #22-21E well will directionally drilled from the existing RBU #11-21EX well pad. Therefore, the proposed access and pipeline is the access and pipeline associated with the RBU #11-21EX well pad.

A moderate scatter of modern trash (plastic bottles, sanitary food cans, miscellaneous metal, wire, green, brown and clear glass bottles and bottle fragments, foam insulation, etc.) can be found on and surrounding the existing well pads and along the existing oil and gas field service roads in the River Bend Unit area.

Sediments on and surrounding the proposed well pad, and along its access and pipeline are shallow. Therefore, the possibility of buried and/or intact cultural materials on the proposed well pad or along its access and pipeline is low. Therefore, no

additional archaeological work is necessary and clearance is recommended for the construction of the River Bend Unit #22-21E well pad, its access, and pipeline.

REFERENCES CITED

- Childs, O.E.
 - 1950 Geologic history of the Uinta Basin, Utah Geological and Mineralogical Survey. Guidebook to the Geology of Utah, No. 5:49-59.
- Stokes, William D.
 - 1986 Geology of Utah. Contributions by the Utah Museum of Natural History, and the Utah Geological and Mineral Survey Department of Natural Resources. <u>Utah Museum of Natural History</u>, Occasional Papers, No. 6.
- Thornbury, William D.
 - 1965 Regional Geomorphology of the United States. John Wiley & Sons, Inc.
- Truesdale, James A., Kathleen E Hiatt, and Clifford Duncan
 1995 Cultural Resource Inventory of the Proposed Ouray
 Gravel Pit Location, Uintah-Ouray Ute Reservation,
 Uintah County, Utah. Report prepared for U & W
 Construction, Ft. Duchesne, Utah by AIA, Laramie,
 Wyoming.

PALEONTOLOGY EVALUATION SHEET

PROJECT: XTO Energy, Inc. – RBU #22-21E, RBU #27-21E, and RBU #28-21E

LOCATION: Twelve miles southwest of Ouray, Uintah County, Utah. Section 21, 2133' FSL 1975' FEL, T10S, R19E, S.L.B.&M.

OWNERSHIP: PRIV[] STATE[] BLM[X] USFS[] NPS[] IND[] MIL[] OTHER[]

DATE: April 11, 2008

GEOLOGY/TOPOGRAPHY: Rock outcrops in this area are the lower part of Uinta Formation, Eocene age. The area is of moderate to low relief, but drops off to the south into a draw. These wells are on a pad that has already been constructed, but not drilled. It is being expanded with a larger pit and pad to the south.

PALEONTOLOGY SURVEY: YES [] NO Survey [] PARTIAL Survey [X] Surveyed the new area well pad is being expanded to.

SURVEY RESULTS: Invertebrate [] Plant [] Vertebrate [] Trace [] No Fossils Found [X]

PALEONTOLOGY SENSITIVITY: HIGH [] MEDIUM [] LOW [X] (PROJECT SPECIFIC)


MITGATION RECOMMENDATIONS: NONE [X] OTHER [] (SEE BELOW)


No recommendations are being bade for paleontology on these wells.

There is always some potential for discovery of significant paleontological resources in the Uinta Formation. If significant vertebrate fossils (mammals, crocodiles, complete turtle shells, etc.) are encountered during construction, work should stop in that area and a paleontologist should be contacted to evaluate the material discovered.

PALEONTOLOGIST: Alden H. Hamblin

A.H. Hamblin Paleontological Consulting, 3793 N. Minersville Highway, Cedar City, Utah 84720 (435) 867-8355 Utah State Paleontological Permit # 07-355, BLM paleontological Resources Permit # UT-S-05-02, Utah Professional Geologist License – 5223011-2250.





XTO ENERGY, INC. RBU #22-21E,27-21E,28-21E

LOCATED IN UINTAH COUNTY, UTAH SECTION 21, T10S, R19E, S.L.B.&M.




PHOTO: VIEW FROM CORNER #5 TO LOCATION STAKE

CAMERA ANGLE: SOUTHWESTERLY




PHOTO: VIEW OF EXISTING ACCESS

CAMERA ANGLE: SOUTHERLY




Uintah Engineering & Land Surveying 85 South 200 East Vernal, Utah 84078 435-789-1017 uels@uelsinc.com


LOCATION PHOTOS


MONTH DAY


РНОТО


TAKEN BY: B.B. DRAWN BY: Z.L. | REVISED: 00-00-00















ADD DECETAED. 00/25/2000		DI NO ACCIO	MED. 43 04:	7 40275	
APD RECEIVED: 09/25/2008	A	PI NO. ASSIG		7-40375	
WELL NAME: RBU 22-21E			105 500 450	-	
OPERATOR: XTO ENERGY INC (N2615)	PHO	NE NUMBER:	435-722-452	<u>1</u>	
CONTACT: DON HAMILTON					
PROPOSED LOCATION:	INS	SPECT LOCATN	BY: /	/	
NESW 21 100S 190E SURFACE: 2133 FSL 1975 FWL	Tec	ch Review	Initials	Date	
SORFACE: 2133 FSL 1973 FWL W BOTTOM: 2570 FNL 1650 FWL	Eng	gineering			
COUNTY: UINTAH	Geo	ology			
LATITUDE: 39.93127 LONGITUDE: -109.7888 UTM SURF EASTINGS: 603492 NORTHINGS: 4420	521 Su	rface			
FIELD NAME: NATURAL BUTTES (630)				
LEASE TYPE: 1 - Federal LEASE NUMBER: UTU-013766 SURFACE OWNER: 1 - Federal	COA	POSED FORMAT		VD	
RECEIVED AND/OR REVIEWED: Plat Bond: Fed[1] Ind[] Sta[] Fee[]	R649-				
(No. UTB-000138)		ER BEND 🕊			
Potash (Y/N)		-3-2. Gener ng: 460 From Qt		Potwoon Wolls	
Oil Shale 190-5 (B) or 190-3 or 190-13				setween wells	
Water Permit (No. 43-10991)		R649-3-3. Exception			
RDCC Review (Y/N)		Drilling Unit			
(Date:)	1	Board Cause No: 259-01 Eff Date: 250-06			
<i>LUn</i> Fee Surf Agreement (Y/N)	Sit	ing: 460' fr 1	Lbd of Flinc	omm. Tracts	
<u>Mm</u> Intent to Commingle (Y/N)	R649-	-3-11. Dire	ctional Dri	11	
COMMENTS:	<u> </u>				
STIPULATIONS: 1- Edina (M	pprovide				




API Number: 4304740375 Well Name: RBU 22-21E


Township 10.0 S Range 19.0 E Section 21

Meridian: SLBM Operator: XTO ENERGY INC











MICHAEL R. STYLER
Executive Director

Division of Oil Gas and Mining

JOHN R. BAZA Division Director

October 9, 2008

XTO Energy, Inc. P O Box 1360 978 North Crescent Rd. Roosevelt, UT 84066

Re:

RBU 22-21E Well, Surface Location 2133' FSL, 1975' FWL, NE SW, Sec. 21,

T. 10 South, R. 19 East, Bottom Location 2570' FNL, 1650' FWL, SE NW, Sec. 21,

T. 10 South, R. 19 East, Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann.§ 40-6-1 *et seq.*, Utah Administrative Code R649-3-1 *et seq.*, and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-40375.

Sincerely,

Gil Hunt

Associate Director

pab Enclosures

cc:

Uintah County Assessor

Bureau of Land Management, Vernal Field Office



Operator:	XTO E	nergy, Inc.		
Well Name & Number	RBU 22	2-21E		
API Number:	43-047-	40375		
Lease:	UTU-013766			
Surface Location: NE SW Bottom Location: SE NW	Sec. 21 Sec. 21	T. <u>10 South</u> T. <u>10 South</u>	R. 19 East R. 19 East	

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

Contact Carol Daniels at (801) 538-5284

Notify the Division prior to commencing operations to plug and abandon the well.

• Contact Dustin Doucet at (801) 538-5281 (801) 733-0983 home

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- 4. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.
- 5. In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.



2580 Creekview Road Moab, Utah 84532 435/719-2018 435/719-2019 Fax

43-047.40375

October 23, 2008

Fluid Minerals Group Bureau of Land Management Vernal Field Office 170 South 500 East Vernal, Utah 84078

RE: Corrected Pages – Application for Permit to Drill—XTO Energy, Inc. RBU 22-21E

Surface Location: 2,133' FSL & 1,975' FWL, NE/4 SW/4,
Target Location: 2,570' FNL & 1,650' FWL, SE/4 NW/4,
Section 21, T10S, R19E, SLB&M, Uintah County, Utah

Dear Fluid Minerals Group:

On behalf of XTO Energy, Inc. Buys & Associates, Inc. respectfully submits the following corrected pages to replace those pages previously submitted. The pages reflect a correct bottomhole quarter quarter of SE/4 NW/4 on the cover letter, APD cover and fist page of the surface use plan with all other information remaining unchanged. Please replace the pages within the previously submitted APD with the following updated pages.

We apologize for any confusion this may have caused. Please feel free to contact myself or Ken Secrest of XTO Energy, Inc. at 435-722-4521 if you have any questions or need additional information.

Sincerely,

Don Hamilton

Agent for XTO Energy, Inc.

cc: Diana Mason, Division of Oil, Gas and Mining Ken Secrest, XTO Energy, Inc.

RECEIVED OCT 27 2008

DIV. OF OIL, GAS & MINING

FILE COPY



2580 Creekview Road Moab, Utah 84532 435/719-2018 435/719-2019 Fax

September 22, 2008

Fluid Minerals Group Bureau of Land Management Vernal Field Office 170 South 500 East Vernal, Utah 84078

RE: Application for Permit to Drill—XTO Energy, Inc.

RBU 22-21E

Surface Location: 2,133' FSL & 1,975' FWL, NE/4 SW/4,
Target Location: 2,570' FNL & 1,650' FWL, SE/4 NW/4,
Section 21, T10S, R19E, SLB&M, Uintah County, Utah

Dear Fluid Minerals Group:

On behalf of XTO Energy, Inc. Buys & Associates, Inc. respectfully submits the enclosed original and three copies of the Application for Permit to Drill (APD) for the above referenced BLM surface and mineral directional well. The location of the surface and target location as well as all points along the intended well bore path are within Cause No. 259-01 and are not within 460 feet of any uncommitted tracts or the unit boundary. A letter from XTO Energy immediately follows this letter to charge the APD processing fee under the Fiscal Year 2008 Consolidated Appropriations Act. Included with the APD is the following supplemental information:

Exhibit "A" - Survey plats, layouts and photos of the proposed well site;

Exhibit "B" - Proposed location maps with access and utility corridors;

Exhibit "C" - Production site layout;

Exhibit "D" - Directional Drilling Plan with Directional Survey

Exhibit "E" - Surface Use Plan with APD Certification;

Exhibit "F" - Typical BOP and Choke Manifold diagram;

Exhibit "G" - Cultural and Paleontological Clearance Reports.

Thank you very much for your timely consideration of this application. Please feel free to contact myself or Ken Secrest of XTO Energy, Inc. at 435-722-4521 if you have any questions or need additional information.

Sincerely,

Don Hamilton

Agent for XTO Energy, Inc.

cc: Diana Mason, Division of Oil, Gas and Mining Ken Secrest, XTO Energy, Inc.

Hamilton

RECEIVED OCT 27 2008

Form 3160-3 (February 2005)	OMB N	APPROVED 0. 1004-0137 March 31, 2	,		
UNITED STATES DEPARTMENT OF THE I BUREAU OF LAND MAN.	5. Lease Serial No. UTU-013766				
APPLICATION FOR PERMIT TO I	6. If Indian, Allotee N/A	or Tribe 1	lame		
la. Type of work: ✓ DRILL REENTER			7 If Unit or CA Agre River Bend Un		me and No.
lb. Type of Well: ☐ Oil Well	8. Lease Name and RBU 22-21E	Well No.			
2. Name of Operator XTO Energy, Inc.			9. API Well No.	··· ·	
3a. Address PO Box 1360; 978 North Crescent Road Roosevelt, UT 84066	3b. Phone No. (include area code) 435-722-4521		10. Field and Pool, or Natural Butte		y
4. Location of Well (Report location clearly and in accordance with any	• •		11. Sec., T. R. M. or B	lk. and Sur	vey or Area
At surface 2,133' FSL & 1,975' FWL, NE/4 SW At proposed prod. zone 2,570' FNL & 1,650' FWL, SE/4 NV	•		Section 21, T1	0S, R19E	, SLB&M
 Distance in miles and direction from nearest town or post office* 12.37 miles southwest of Ouray, Utah 			12. County or Parish Uintah		13. State UT
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any) 1,975'	16. No. of acres in lease 17. Spacing Unit dedicated to this well 2,240 acres 40 acres			well	
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20'	19. Proposed Depth 8,583' MD, 8,500' TVD		/BIA Bond No. on file 3-000138		
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 5,188' GR	22 Approximate date work will sta 12/15/2008	rt*	23. Estimated duratio 14 days	n	
	24. Attachments				
 The following, completed in accordance with the requirements of Onshord Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest System I SUPO must be filed with the appropriate Forest Service Office). 	4. Bond to cover to Item 20 above). Lands, the 5. Operator certification	he operation	is form: ns unless covered by an ormation and/or plans as	J	·
25. Signature Don Hamilton	Name (Printed/Typed) Don Hamilton			Date 09/2	2/2008
Title Agent for XTO Energy, Inc.					
Approved by (Signature)	Name (Printed/Typed)			Date	- 1, , , , , , , , , , , , , , , , , , ,
Title	Office				
Application approval does not warrant or certify that the applicant holds conduct operations thereon. Conditions of approval, if any, are attached.	s legal or equitable title to those righ	ts in the sub	ject lease which would o	entitle the a	pplicant to
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a cr. States any false, fictitious or fraudulent statements or representations as t	ime for any person knowingly and on ony matter within its jurisdiction.	willfully to m	nake to any department of	or agency	of the United

*(Instructions on page 2)

RECEIVED OCT 27 2008

SURFACE USE PLAN

Name of Operator: XTO Energy, Inc.

Address: PO Box 1360; 978 North Crescent Road

Roosevelt, Utah 84066

Well Location: RBU 22-21E

Surface Location: 2,133' FSL & 1,975' FWL, NE/4 SW/4, Target Location: 2,570' FNL & 1,650' FWL, SE/4 NW/4, Section 21, T10S, R19E, SLB&M, Uintah County, Utah

The surface owner or surface owner representative and dirt contractor will be provided with an approved copy of the surface use plan of operations and approved conditions of approval before initiating construction.

The onsite inspection for the referenced well was conducted on Tuesday, April 29, 2008 at approximately 2:21 pm. In attendance at the onsite inspection were the following individuals:

Karl Wright BLM - Vernal Field Office Natural Resource Specialist Brandon McDonald Wildlife Biologist BLM - Vernal Field Office Floyd Bartlett DOGM - Roosevelt Field Office Inspector **Uintah Engineering & Land Surveying** Brandon Bowthorpe Surveyor Randy Jackson Foreman **Jackson Construction** Billy McClure LaRose Construction Foreman

Jody MechamEngineerXTO Energy Inc.Ken SecrestRegulatory CoordinatorXTO Energy, Inc.

1. Location of Existing Roads:

- a. The proposed well site is located approximately 27.37 miles southwest of Ouray, Utah.
- b. Directions to the proposed well site have been attached at the end of Exhibit B.
- c. The use of roads under State and County Road Department maintenance are necessary to access the River Bend Unit area. However, an encroachment permit is not anticipated since no upgrades to the State or County Road system are proposed at this time.
- All existing roads will be maintained and kept in good repair during all phases of operation.
- Vehicle operators will obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions.
- f. Since no improvements are anticipated to the State, County, Tribal or BLM access roads no topsoil striping will occur.
- g. An off-lease federal Right-of-Way is not anticipated for the access road and utility corridors since both are located entirely within the River Bend Unit area.

STATE OF UTAH		FORM 9	
			5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-013766
SUNDF	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	sals to drill new wells, significantly deepen igged wells, or to drill horizontal laterals. l		7.UNIT or CA AGREEMENT NAME: RIVER BEND
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: RBU 22-21E
2. NAME OF OPERATOR: XTO ENERGY INC			9. API NUMBER: 43047403750000
3. ADDRESS OF OPERATOR: 382 Road 3100 , Aztec, NM, 8	7410 505 333-3159 Ext	PHONE NUMBER:	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NESW Section: 21	(P, RANGE, MERIDIAN: Township: 10.0S Range: 19.0E Meridian:	S	COUNTY: UINTAH STATE: UTAH
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPORT	, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	☐ ACIDIZE	ALTER CASING	CASING REPAIR
✓ NOTICE OF INTENT Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS	CHANGE TUBING	☐ CHANGE WELL NAME
10/9/2010	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	☐ NEW CONSTRUCTION
Date of Work Completion.	OPERATOR CHANGE	PLUG AND ABANDON	☐ PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	☐ TUBING REPAIR	VENT OR FLARE	☐ WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
• • • • • • • • • • • • • • • • • • • •	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:
	MPLETED OPERATIONS. Clearly show all perests a one year extension on tests a referenced well.	the state permit for the	Approved by the Utah Division of Oil, Gas and Mining Date: October 05, 2009 By:
NAME (PLEASE PRINT) Eden Fine	PHONE NUMBER 505 333-3664	TITLE Permitting Clerk	
SIGNATURE N/A		DATE 10/1/2009	



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000 Well Name: RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC

Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not req

require revi	sion. Following is a che	cklist of some ite	ms related to the	application, w	hich should be verified.
	ated on private land, ha ed? 💮 Yes 📵 No	s the ownership	changed, if so, ha	s the surface a	greement been
	any wells been drilled i requirements for this l			which would a	ffect the spacing or
	nere been any unit or of s proposed well? 📋 Y		put in place that	could affect the	e permitting or operation
	there been any changes the proposed location?		_	nership, or righ	tof- way, which could
• Has th	ne approved source of v	vater for drilling	changed? 🔘 Ye	es 🖲 No	
	there been any physica le in plans from what w				
• Is bor	nding still in place, whic	ch covers this pro	posed well? 🌘	Yes 📗 No U	pproved by the Itah Division of , Gas and Mining
Signature:	Eden Fine	Date: 10/1/2009	9		
Title:	Permitting Clerk Repres	enting: XTO ENER	GY INC		October 05, 2009
				J.	00. cat 110

	STATE OF UTAH	F6			FORM 9
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING			5		E DESIGNATION AND SERIAL NUMBER: 113766
SUND	RY NOTICES AND REPORTS	ON	WELLS	6. IF II	NDIAN, ALLOTTEE OR TRIBE NAME:
	sals to drill new wells, significantly deepen ugged wells, or to drill horizontal laterals. U				or CA AGREEMENT NAME: BEND
1. TYPE OF WELL Gas Well					L NAME and NUMBER: 2-21E
2. NAME OF OPERATOR: XTO ENERGY INC					NUMBER: 2403750000
3. ADDRESS OF OPERATOR: 382 Road 3100 , Aztec, NM, 8			JMBER:		D and POOL or WILDCAT: RAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL				COUNT	
QTR/QTR, SECTION, TOWNSHI	IP, RANGE, MERIDIAN: Township: 10.0S Range: 19.0E Meridian:	S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NA	ATURE OF NOTICE, REPORT,	OR OT	HER DATA
TYPE OF SUBMISSION			TYPE OF ACTION		
	☐ ACIDIZE		ALTER CASING		CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS		CHANGE TUBING		CHANGE WELL NAME
9/28/2011	☐ CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS		CONVERT WELL TYPE
SUBSEQUENT REPORT	☐ DEEPEN	☐ F	FRACTURE TREAT		NEW CONSTRUCTION
Date of Work Completion:	☐ OPERATOR CHANGE	☐ F	PLUG AND ABANDON		PLUG BACK
	☐ PRODUCTION START OR RESUME	☐ F	RECLAMATION OF WELL SITE		RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	☐ REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL		TEMPORARY ABANDON
	☐ TUBING REPAIR		/ENT OR FLARE		WATER DISPOSAL
☐ DRILLING REPORT	☐ WATER SHUTOFF	□ s	SI TA STATUS EXTENSION	1	APD EXTENSION
Report Date:	☐ WILDCAT WELL DETERMINATION		OTHER	отн	ER:
12. DESCRIBE PROPOSED OR CO	DMPLETED OPERATIONS. Clearly show all per	rtinen	t details including dates, depths, v	volumes,	etc.
XTO hereby reques	sts a one (1) year extension or	n th	e State Permit for the		
	referenced well.				Approved by the
					Utah Division of I, Gas and Mining
				Oi	i, das and Minning
			D	ate:_	September 29, 2010
			_	F	00, cut 110
			В	λ: <u>π</u>	son first
					7.5
NAME (PLEASE PRINT) Kelly Small	PHONE NUMBER 505 333-3145		TITLE Sr. Permitting Tech		
SIGNATURE		-	DATE		
N/A			9/28/2010		



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000 Well Name: RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC

Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

uiie ievi	sion. Following is a	checklist of some items related to the	application, willch should be verified.
	ated on private land ed? 🔵 Yes 📵 N	, has the ownership changed, if so, haso o	s the surface agreement been
		ed in the vicinity of the proposed well is location? (Yes (No	which would affect the spacing or
	nere been any unit o s proposed well?		could affect the permitting or operation
	there been any char the proposed locati	nges to the access route including own on? Yes No	ership, or rightof- way, which could
• Has th	ne approved source	of water for drilling changed? 🔘 Ye	s 📵 No
		sical changes to the surface location or t was discussed at the onsite evaluati	
• Is bor	nding still in place, v	vhich covers this proposed well?	Approved by the Yes No Utah Division of Oil, Gas and Mining
nature:	Kelly Small	Date: 9/28/2010	
	•	Representing: XTO ENERGY INC	Date: September 29, 2010
			J. Decil V

Sig

Sundry Number: 19203 API Well Number: 43047403750000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOURCE		FORM 9
DIVISION OF OIL, GAS, AND MINING			5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-013766
SUNDE	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	sals to drill new wells, significantly deepen igged wells, or to drill horizontal laterals. U		7.UNIT OF CA AGREEMENT NAME: RIVER BEND
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: RBU 22-21E
2. NAME OF OPERATOR: XTO ENERGY INC			9. API NUMBER: 43047403750000
3. ADDRESS OF OPERATOR: 382 Road 3100 , Aztec, NM, 8		NE NUMBER:	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NESW Section: 21	P, RANGE, MERIDIAN: Township: 10.0S Range: 19.0E Meridian:	S	STATE: UTAH
11. CHE	CK APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPORT	, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
_	☐ ACIDIZE	☐ ALTER CASING	CASING REPAIR
Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS	☐ CHANGE TUBING	☐ CHANGE WELL NAME
10/5/2012	☐ CHANGE WELL STATUS	\square commingle producing formations	☐ CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	☐ FRACTURE TREAT	☐ NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE	☐ PLUG AND ABANDON	PLUG BACK
_	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	☐ SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	☐ TUBING REPAIR	☐ VENT OR FLARE	WATER DISPOSAL
☐ DRILLING REPORT	☐ WATER SHUTOFF	☐ SI TA STATUS EXTENSION	✓ APD EXTENSION
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:
	MPLETED OPERATIONS. Clearly show all per equests a one (1) year extensi referenced well.	on of the State APD for th	
NAME (PLEASE PRINT) Krista Wilson	PHONE NUMBER 505 333-3647	TITLE Permitting Tech	
SIGNATURE N/A		DATE 10/5/2011	

Sundry Number: 19203 API Well Number: 43047403750000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000 **Well Name:** RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC

Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

 If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
 Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? 🔘 Yes 📵 No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No

Signature: Krista Wilson Date: 10/5/2011

Title: Permitting Tech Representing: XTO ENERGY INC

Sundry Number: 30539 API Well Number: 43047403750000

STATE OF UTAH DEPARTMENT OF OFTI, GAS, AND MINING SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below report of the proposals of the proposals. TUNTER CRUE JUNTAN CA AGREEMENT NAME: TUNTER CRUE SUNDRY NOTICES AND REPORTS ON WELLS TUNTER CA AGREEMENT NAME: REVER CRUO TUNTER CA AGREEMENT NAME: REVER CRUO SURFACE SUNDRY NOTICES AND PROPOSALS SUNDRY NOTICES AND PROPOSALS AND AGREEMENT NAME: AGAPT 403750000 SPEELD AND PROPOSALS AND AGAPT OF PROPOSALS AGAPT OF PRO				
DIVISION OF OIL, GAS, AND MINING SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-fold depth, rearrier byggged wells, or to drill horizontal laterals. Use APPLICATION ROPE PERMIT TO BRILL form for such proposals. 1. TYPE OF MELL TO BRILL form for such proposals. 2. NAME OF OPERATOR: 3. PHONE NUMBER: 3. PHONE NUMBER: 4. WELL NAME and NUMBER: 8. WELL NAME: 8. WELL NAME and NUMBER: 8. WELL NAME and NUME				FORM 9
Do not use this form for proposals to drill new wells, significantly despen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION PROPERTY TO DRILL form for such proposals. 1. TYPE OF WELL GISTON C				
CONTROL DOTRILL FOR TOP SUBJECT TO DRILL FOR THE PLUGGED Wells, or to drill horizontal laterals. Use APPLICATION NUCK BEND	SUNDF	RY NOTICES AND REPORTS (ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Sas Well 2. NAME OF OPERATOR: XTO ENERGY INC 3. ADDRESS OF OPERATOR: XTO ENERGY INC 3. ADDRESS OF OPERATOR: XTO ENERGY INC 3. ADDRESS OF OPERATOR: XTO ENERGY INC 4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL OTRIOTIR. SETUTOR. TOWNSHIP, RANGE, MERIDIAN: OTRIOTIR. NESTWO Section. 21 Township: 10.05 Range: 19.0E Meridian: S 11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION INCREME PROPORT INCREMENTATION ORDINATE STATE UITAM TO SUBMISSION TYPE OF ACTION ORDINATE STATE UITAM TYPE OF SUBMISSION TYPE OF ACTION ORDINATE STATE UITAM TYPE OF SUBMISSION TYPE OF ACTION ORDINATE STATE UITAM TYPE OF SUBMISSION TYPE OF ACTION ORDINATE STATE UITAM TYPE OF SUBMISSION TYPE OF ACTION ORDINATE STATE UITAM TYPE OF SUBMISSION TYPE OF ACTION ORDINATE STATE O	current bottom-hole depth,	reenter plugged wells, or to drill horizon		
ADDRESS OF OPERATOR: 3. ADDRESS OF OPERATOR: 4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FVL. 4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FVL. 4. COLORY: 2133 FSL 1975 FVL. 5. ADDRESS OF OPERATOR: 2133 FSL 1975 FVL. 2133 FSL				1
382 ROAd 3100, Aztec, NM, 87410 505 333-3145 Ext NATURA BUTTES LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1907 FWL OTROUTS, SECTION, TOWNSHIP, RANGE, MERIDIAN: QUIVOUR, NESW Section: 21 Township: 10.05 Range: 19.0E Meridian: S TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION ACROST ACROS				· · · · · · · · · · · · · · · · · · ·
FOOTAGES AT SURFACE: 21/33 FSL 1975 FWL OTRIGITS, SECTION, TOWNSHIP, RANGE, MERIDIAN: OTIVICIT. NESW Section: 21 Township: 10.0S Range: 19.0E Meridian: S TYPE OF SUBMISSION TYPE OF ACTION CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION				I .
TATE: UTAH 11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE ALTER CASING CARNG REPAR CHANGE TURING CARNG REPAR CHANGE WILL KAME CHA	FOOTAGES AT SURFACE:			1
TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE	QTR/QTR, SECTION, TOWNS		an: S	1
ANDICE OF INTENT ASJOCATIONS DESCRIPTION AS CARRING PROPERTY BY NOTICE OF INTENT OF I		K APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
AND TICE OF INTEXT APPORTING SEE WORK WILL STATUS SUBSEQUENT REPORT Date of Spud: GRANGE PREVIOUS PLANS CHANGE WELL STATUS COMMINGLE PRODUCING FORMATIONS CONVERT WELL TYPE	TYPE OF SUBMISSION		TYPE OF ACTION	
Approximate date work will start: 8/31/2013	A MOTIOS OS MITEMIS	ACIDIZE	ALTER CASING	CASING REPAIR
CAMAGE WELL STATUS SUBSECUENT REPORT Date of Work Completion: CHANGE WELL STATUS CHANGE WELL STATUS CHANGE WELL STATUS CHANGE WELL STATUS CHANGE WELL STATUS WE CONSTRUCTION PRUD AND ABANDON PRUD BACK PRODUCTION START OR RESUME RECLAMATION OF WELL SITE RECOMPLETE DIFFERENT FORMATION SPUD REPORT CHANGE WELL STATUS EXTENSION WATER DISPOSAL ORILLING REPORT WATER SHUTOFF SITA STATUS EXTENSION WATER SHUTOFF WILDCAT WELL DETERMINATION OTHER OTHER OTHER 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. XTO Energy requests a one (1) year extension of the State APD for the referenced well. NAME (PLEASE PRINT) PHONE NUMBER REQUISITION REPORT RECOMPLETE DIFFERENT FORMATION OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OCTOBER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER	Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
Date of Work Completion: OPERATOR CHANGE	0,01,2010	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SPUD REPORT Date of Spud: REPERFORATE CURRENT FORMATION SIDETRACK TO REPAIR WELL TEMPORARY ABANDON		DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
SPUD REPORT Date of Spud: REPERFORATE CURRENT FORMATION SIDETRACK TO REPAIR WELL TEMPORARY ABANDON TUBING REPAIR VENT OR FLARE WATER DISPOSAL APD EXTENSION APD EXTENSION OTHER: TUBING REPORT Report Date: WATER DISPOSAL VENT OR FLARE WATER DISPOSAL VARIOUS PORT TUBING REPAIR VENT OR FLARE WATER DISPOSAL VARIOUS PORT VENT OR FLARE WATER DISPOSAL VARIOUS PORT VENT OR FLARE WATER DISPOSAL VARIOUS PORT VARIOUS PORT VENT OR FLARE WATER DISPOSAL VARIOUS PORT VARIOUS PORT VARIOUS PORT VARIOUS PORT VARIOUS PORT VENT OR FLARE WATER DISPOSAL VARIOUS PORT VARIOUS PORT VARIOUS PORT VARIOUS PORT VARIOUS PORT VENT OR FLARE VARIOUS PORT VAR		OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
Tubing Repair □ DRILLING REPORT Report Date: □ WATER SHUTOFF □ OTHER: □ MATER DISPOSAL □ APD EXTENSION OTHER: □ MATER DISPOSAL □ APD EXTENSION OTHER: □ WATER DISPOSAL □ APD EXTENSION OTHER: □ WATER DISPOSAL	SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
DRILLING REPORT Report Date: WILDCAT WELL DETERMINATION OTHER: 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. XTO Energy requests a one (1) year extension of the State APD for the referenced well. NAME (PLEASE PRINT) Richard L. Redus 303 397-3712 PHONE NUMBER Regulatory SIGNATURE DATE	Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
NAME (PLEASE PRINT) Richard L. Redus Name (PLEASE PRINT) Richard L. Redus 303 397-3712 Regulatory DATE OTHER IIILE Regulatory DATE		TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. XTO Energy requests a one (1) year extension of the State APD for the referenced well. Approved by the Utah Division of Oil, Gas and Mining Date: October 11, 2012 By: NAME (PLEASE PRINT) PHONE NUMBER Regulatory Richard L. Redus 303 397-3712 SIGNATURE DATE		WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
XTO Energy requests a one (1) year extension of the State APD for the referenced well. Approved by the Utah Division of Oil, Gas and Mining Date: October 11, 2012 By: NAME (PLEASE PRINT) PHONE NUMBER Richard L. Redus 303 397-3712 Regulatory SIGNATURE DATE		WILDCAT WELL DETERMINATION	OTHER	OTHER:
Richard L. Redus 303 397-3712 Regulatory SIGNATURE DATE		sts a one (1) year extension of		Approved by the Utah Division of Oil, Gas and Mining Date: October 11, 2012
SIGNATURE DATE				
	SIGNATURE		DATE	

Sundry Number: 30539 API Well Number: 43047403750000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000 Well Name: RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision.

owing is a checklist of some items related to the application, which should be verified.
• If located on private land, has the ownership changed, if so, has the surface agreement been updated? — Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of thi proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? (Yes (No
• Has the approved source of water for drilling changed? Yes No
• Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? 🌘 Yes 🔘 No
nature: Richard L. Redus Date: 10/3/2012

Sig Title: Regulatory Representing: XTO ENERGY INC Sundry Number: 43481 API Well Number: 43047403750000

	STATE OF UTAH		FORM 9
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING			5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-013766
SUNDF	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	oposals to drill new wells, significantly reenter plugged wells, or to drill horizo n for such proposals.		7.UNIT or CA AGREEMENT NAME: RIVER BEND
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: RBU 22-21E
2. NAME OF OPERATOR: XTO ENERGY INC			9. API NUMBER: 43047403750000
3. ADDRESS OF OPERATOR: PO Box 6501, Englewood,	CO, 80155 303 397-3	PHONE NUMBER: 3727 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 21 Township: 10.0S Range: 19.0E Merio	dian: S	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
/	ACIDIZE	ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start: 7/7/2014	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
7/1/2014	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION
	WILDCAT WELL DETERMINATION	OTHER	OTHER:
I .	completed operations. Clearly show sts a one (1) year extension of referenced well.		Approved by the Utah Division of Oil, Gas and Mining Date: October 16, 2013 By:
NAME (PLEASE PRINT) Sephra Baca	PHONE NUMB 719 845-2103	ER TITLE Regulatory Analyst	
SIGNATURE N/A		DATE 10/8/2013	

Sundry Number: 43481 API Well Number: 43047403750000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000

Well Name: RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? (Yes (No
• Has the approved source of water for drilling changed? Yes No
• Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No

Signature: Sephra Baca Date: 10/8/2013
Title: Regulatory Analyst Representing: XTO ENERGY INC



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
Green River District
Vernal Field Office
170 South 500 East
Vernal, UT 84078
http://www.blm.gov/ut/st/en/fo/vernal.html



APR 14 2014

IN REPLY REFER TO: 3160 (UTG011)

Malia Villers XTO Energy, Inc. PO Box 6501 Englewood, CO 80155

43 047 40375

Re: Request to Return APD
Well No. RBU 22-21E
NESW, Sec. 21, T10S, R19E
Uintah County, Utah
Lease No. UTU-013766
River Bend Unit

RECEIVEL NAY 12 2014

MAY 12 2014

DIV. OF OIL, GAS & MINING

Dear Ms. Villers:

The Application for Permit to Drill (APD) for the above referenced well received in this office on September 23, 2008, is being returned unapproved per your request to this office in an email message to Natural Resource Specialist David Gordon received on February 19, 2014. If you intend to drill at this location at a future date, a new APD must be submitted.

If you have any questions regarding APD processing, please contact Robin R. Hansen at (435) 781-3428.

Sincerely,

/s/ Jerry Kenczka

Jerry Kenczka Assistant Field Manager Lands & Resource Minerals

Enclosures

CC:

UDOGM

bcc:

Well File

Sundry Number: 55752 API Well Number: 43047403750000

	STATE OF UTAH		FORM 9	
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING			5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-013766	
SUNDR	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.			7.UNIT or CA AGREEMENT NAME: RIVER BEND	
1. TYPE OF WELL Gas Well	8. WELL NAME and NUMBER: RBU 22-21E			
2. NAME OF OPERATOR: XTO ENERGY INC	9. API NUMBER: 43047403750000			
3. ADDRESS OF OPERATOR: PO Box 6501 , Englewood,		PHONE NUMBER: 727 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2133 FSL 1975 FWL	COUNTY: UINTAH			
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: NESW Section: 21 Township: 10.0S Range: 19.0E Meridian: S			STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	ACIDIZE	ALTER CASING	CASING REPAIR	
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
9/30/2015	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT Date of Work Completion:	L DEEPEN	FRACTURE TREAT	☐ NEW CONSTRUCTION	
	☐ OPERATOR CHANGE	PLUG AND ABANDON	L PLUG BACK	
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	L TEMPORARY ABANDON	
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
Nopon Suio.	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
l .	COMPLETED OPERATIONS. Clearly show a sts a one (1) year extension of referenced well.	f the State APD for the	<u>'</u>	
Malia Villers	303 397-3670	Lead Permitting Analyst		
SIGNATURE N/A		DATE 9/18/2014		

Sundry Number: 55752 API Well Number: 43047403750000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047403750000

API: 43047403750000

Well Name: RBU 22-21E

Location: 2133 FSL 1975 FWL QTR NESW SEC 21 TWNP 100S RNG 190E MER S

Company Permit Issued to: XTO ENERGY INC Date Original Permit Issued: 10/9/2008

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If loca Yes(wnership changed, if so, ha	as the surface agreement been updated? 🔵
	any wells been drilled in the vertical terms and the vertical terms are the second second to the second sec		ll which would affect the spacing or siting
	nere been any unit or other ag sed well? 🤵 Yes 🍺 No	reements put in place that	could affect the permitting or operation of this
		e access route including ow No	wnership, or rightof- way, which could affect the
• Has th	ne approved source of water f	or drilling changed? 🔵 🕦	Yes 📵 No
	there been any physical chang from what was discussed at t		or access route which will require a change in Yes No
• Is bon	ding still in place, which cove	ers this proposed well? 🌘	Yes 🔘 No
Signature:	Malia Villers	Date: 9/18/2014	





MICHAEL R. STYLER

Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

October 15, 2015

Malia Villers XTO Energy Inc. P.O. BOX 6501 Englewood, CO 80155

43-047-40375

Re: APDs Rescinded for XTO Energy Inc., Uintah County

Dear Ms. Villers:

Enclosed find the list of APDs that you asked to be rescinded. No drilling activity at these locations has been reported to the division. Therefore, approval to drill these wells is hereby rescinded effective October 9, 2015.

A new APD must be filed with this office for approval <u>prior</u> to the commencement of any future work on the subject location.

If any previously unreported operations have been performed on this well location, it is imperative that you notify the Division immediately.

Sincerely,

Environmental Scientist

cc:

Well File

Bureau of Land Management, Vernal



Operator [*]	API Number	Well Name	Work Type	Date Approved	Date Permit Will Expire:
XTO ENERGY INC	4304739647	RBU 16-20F	DRILL	10/04/2007	10/04/2015
XTO ENERGY INC	4304740375	RBU 22-21E	DRILL	10/09/2008	10/09/2015
XTO ENERGY INC	4304740376	RBU 27-21E	DRILL	10/09/2008	10/09/2015
XTO ENERGY INC	4304740377	RBU 28-21E	DRILL	10/09/2008	10/09/2015
XTO ENERGY INC	4304738676	LCU 12-9H	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738677	LCU 6-9H	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738678	LCU 4-11H	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738679	LCU 9-12H	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738682	LCU 14-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738683	LCU 13-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738684	LCU 10-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738685	LCU 5-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738686	LCU 4-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738687	LCU 7-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304738688	LCU 3-6G	DRILL	10/12/2006	10/12/2015
XTO ENERGY INC	4304740388	RBU 1-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740389	RBU 2-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740390	RBU 6-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740391	RBU 7-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740392	RBU 8-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740393	RBU 9-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740394	RBU 12-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740395	RBU 15-3F	DRILL	10/15/2008	10/15/2015
XTO ENERGY INC	4304740397	HCU 4-30F	DRILL	10/16/2008	10/16/2015
XTO ENERGY INC	4304737285	LCU 11-17H	DRILL	10/25/2005	10/25/2015
XTO ENERGY INC	4304737286	LCU 7-17H	DRILL	10/25/2005	10/25/2015